

Product Data Sheet

GENFAST™ 3" MAX SEAM PLATE



Description

GenFast™ 3" (76 mm) MAX Seam Plate is a round, metal, barbed seam plate to be used with the GenFast #16 MAX Fastener. The eyehooks are unique grips that hold the membrane with minimal tearing. GenFast 3" (76 mm) MAX Seam Plate has an extruded center hole for increased pull through resistance.

GenFlex GenFast 3" (76 mm) MAX Seam Plates may be used to secure GenFlex TPO membrane to the roof deck in GenFlex TPO. Please refer to current GenFlex TPO specifications and details for specific applications.

Item Number: 51006

Physical Properties

PROPERTIES	MINIMUM PERFORMANCE
Metal	AZ 55 Galvalume®
Diameter	3" (76mm)
Thickness	20 Gauge (0.037")
Edges	All edges are deburred

Method of Application

1. GenFlex Roofing Systems recommends the use of a 6.5 Amp (min.), 0-2,500 RPM (max.) Screw gun for installation of GenFlex GenFast 3" (76 mm) MAX Seam Plates and GenFast #16 MAX Fastener.
2. Check current GenFlex specifications for exceptions and/or changes.

Product Data

PACKAGING	QUANTITY
Bucket	500 Pieces

Compliance

Recycled Content

Post Consumer	0%
Pre Consumer	0%



Storage

Fasteners should be protected from moisture and kept dry at all times.

If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

Eye protection is recommended when installing fasteners and plates.

Seam Plates are manufactured from galvanized metal. Precautions should be taken to avoid metal slivers, etc.

Refer to Material Safety Data Sheet for further information.