

GenFlex Cleaner

DESCRIPTION

GenFlex Cleaner is required to clean the GenFlex EPDM membrane prior to applying splice adhesive.

GenFlex Cleaner is required to clean GenFlex TPO membrane before splicing when contaminants prohibit a proper weld.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Composition	Napthinic Solvents
Color	Clear
Solids	0.0%
Viscosity	Free Flowing
Weight	6.25 ± .25 lb/gal (.77 ± 0.05 kg/L)

INSTALLATION

1. Apply liberal amounts of Cleaner to clean rag.
2. Using a scrubbing motion, remove all contaminants at least 2" (50 mm) each way from the area to be spliced.
3. Remove all visible contaminants and maintain surfaces free from all moisture, oil, and other contaminants.
4. Change rags frequently to avoid depositing previously removed materials.
5. Allow the cleaned membrane to dry completely before seaming.

PRODUCT DATA

Container Size: 5 gallon (18.9 Liter) Pail

GenFlex Product #: 10093

Flash Point: 45 °F (-12 °C) TCC

Coverage Rate: Correctly applied, 1 gallon (3.8 L) of bonding adhesive will cover approximately 60 - 70 sq ft (5.6 m² - 6.5 m²) of finished surface.

Tolerance Limit:

Naptha 500 parts per million in air

LEED INFORMATION

Recycled Content

Post Consumer 0%

Post Industrial 0%

V.O.C. Content 750 g/L

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.



SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

Open all doors and windows.

Close containers after use.

Use with adequate ventilation.

Avoid prolonged breathing of vapors.

Avoid prolonged and repeated contact with skin.

Store at temperature of 80 °F (27 °C) or below for maximum shelf life.

Keep out of reach of children.

Keep away from eyes.

Use chemically resistant gloves.

Review Material Safety Data Sheet prior to use.