

FlexWhite™ Edge Caulk



DESCRIPTION

GenFlex FlexWhite Edge Caulk is a high quality one-part elastomeric sealant that is used primarily to seal the outside edge of FlexWhite Peel & Stick flashing products. It offers excellent adhesion to both EPDM and TPO membranes and has excellent weathering resistance to ozone and ultra-violet light.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Base	EPDM Rubber
Color	White
Solids	80%
UV & Ozone Resistance	Excellent
Specific Gravity	1.40 – 1.46
Cure System	Solvent Based

INSTALLATION

Refer to current GenFlex Technical Specifications for additional application instructions.

IMPORTANT: Ensure the receiving surfaces are free of debris and no moisture is present.

1. Apply GenFlex FlexWhite Edge Caulk at a coverage rate of 15 feet (4.6 m) of 3/8" x 1/4" (9.5 mm x 6.3 mm) continuous bead per tube, according to current GenFlex specifications and details.
2. Apply a continuous "high profile" bead of FlexWhite Edge Caulk to the entire outside edge of the FlexWhite Peel & Stick flashing products (FlexWhite Corners, T-Joints, Cover Tape, etc.).
3. GenFlex FlexWhite Edge Caulk may be used at other details using Cover Tape, including curb or skylights, pitch pans, scuppers, perimeter edge metal, and gutters.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
11 oz (326 mL) Tube	12 Tubes per Carton	W590030105

Coverage Rate: 15' (4.6 m) per tube

LEED INFORMATION

Recycled Content:

Post Consumer 0%

Post Industrial 0%

V.O.C. Content: Less than 250 g/L

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

Open all doors and windows.

Close containers after use.

Use with adequate ventilation.

Avoid prolonged breathing of vapors.

Avoid prolonged and repeated contact with skin.

Store at temperature of 80 °F (27 °C) or below for maximum shelf life.

Keep out of reach of children.

Keep away from eyes.

Use chemically resistant gloves.

Review Material Safety Data Sheet prior to use.