

GenFast™ 2" Seam Plate

DESCRIPTION

GenFast™ 2" Seam Plates are designed to be used with GenFlex fasteners to attach GenFlex FRM EPDM and TPO membranes and Reinforced Perimeter Strips to a variety of approved substrates including 22-gauge steel and wood decks. Please refer to current GenFlex EPDM and TPO specifications and details for specific applications.

PHYSICAL PROPERTIES

PROPERTY	MINIMUM PERFORMANCE
Metal	Galvanized G-90
Diameter	2" (51 mm)
Thickness	0.030" (0.8 mm)
Hole Diameter	¼" (6 mm)
Edges	All Edges are Deburred

INSTALLATION

Install GenFlex Seam Plates in accordance with current GenFlex specifications, details, and workmanship requirements.

PRODUCT DATA

PRODUCT #	QUANTITY
W590010074	1000 per bucket

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%



STORAGE

Seam Plates should be protected from moisture and kept dry at all times. If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

SHELF LIFE

Not applicable

PRECAUTIONARY DATA

Eye protection is recommended when installing fasteners and plates.

Seam Plates are manufactured from galvanized metal. Precautions should be taken to avoid metal slivers when handling and during installation.

Refer to Material Safety Data Sheet for additional information.