


GenFast™ #12 Preassembled Screw and Plate

ITEM NUMBER:

2-1/4" W590055114	2-7/8" W590055115
3-1/4" W590055116	3-3/4" W590055117
4-1/2" W590055118	5" W590055119
6" W590055120	7" W590055121
8" W590055122	



Description:

GenFast™ #12 Preassembled Screws and Plates may be used in any GenFlex system for attachment of roofing insulations to steel, wood, and lightweight concrete (into steel deck) substrates.

Method of Application:

1. GenFast #12 Preassembled Screw length is determined as follows:
 - Steel Deck – Minimum of 1" (25 mm) required penetration
 - Wood Deck – Minimum of 1" (25 mm) required penetration
2. Check current GenFlex specifications for exceptions and/or changes.

Storage:

- Fasteners should be protected from moisture and kept dry at all times.
- If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautions:

- Eye protection is recommended when installing fasteners and plates.
- Refer to Material Safety Data Sheet for further information.

Compliance:

Post Consumer Recycled Content: 25%
 Pre Consumer Recycled Content: 0%

Packaging:	Screw Length	Thread Length	Pieces/Carton
	2-1/4"	1-7/8"	250
	2-7/8"	2-5/8"	250
	3-1/4"	2-3/4"	250
	3-3/4"	2-3/4"	250
	4-1/2"	3-1/2"	250
	5"	3-3/4"	250
	6"	3-3/4"	250
	7"	3-3/4"	250
	8"	3-3/4"	250

PRODUCT DATA SHEET



Physical Properties:*Minimum Performance*Screw:

Metal: SAE 1022 Heat Treated
Diameter and Thread: #12 Modified Buttress
Head Style: #3 Phillips
Corrosion Coating: SPEX™
Fastener Tip: Patented X-Point

Plate:

Material: Polypropylene
Diameter: 3" (76 mm) round
Corrosion Coating: Non-corrosive plastic

Please contact the GenFlex Technical Department at 800-443-4272.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.