

## GenFast™ #15 Preassembled Screw and Plate

### ITEM NUMBER:

2"	W590055141	7"	W590055146
3"	W590055142	8"	W590055147
4"	W590055143	10"	W590055148
5"	W590055144	12"	W590055149
6"	W590055145		



### Description:

GenFast™ #15 Preassembled Screws and Plates may be used in any GenFlex system or attachment of roofing membrane to steel, OSB (with acceptable pull test) and plywood.

### Method of Application:

1. GenFast #15 Preassembled Screw length is determined as follows:
  - Steel Deck – Minimum of 1" (25 mm) required penetration
  - Wood Deck – Minimum of 1" (25 mm) required penetration
2. Check current GenFlex specifications for exceptions and/or changes.

### Storage:

- Fasteners should be protected from moisture and kept dry at all times.
- If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

### Precautions:

- Eye protection is recommended when installing fasteners and plates.
- Refer to Material Safety Data Sheet for further information.

### Compliance:

Post Consumer Recycled Content: 25%  
 Pre Consumer Recycled Content: 0%

Packaging:	Screw Length	Thread Length	Pieces/Carton
	2"	Full	250
	3"	Full	250
	4"	3"	250
	5"	4"	250
	6"	4"	250
	7"	4"	250
	8"	4"	250
	10"	4"	200
	12"	4"	200

**Physical Properties:***Minimum Performance*Screw:*Metal:*

SAE 1022 Heat Treated

*Diameter and Thread:*

0.435" Diameter Head and 0.265 Diameter Thread

*Head Style:*

#3 Phillips Truss Head

*Corrosion Coating:*

CR-10

*Fastener Tip:*

Drill Point

Plate:*Material:*

AZ 55 Galvalume®

*Diameter:*

2-3/8" (60.3 mm) round

*Corrosion Coating:*

Meets FM requirements – Less than 15% red rust in 15 cycles of Kesternich Testing (DIN 50018)

Please contact the GenFlex Technical Department at 800-443-4272.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*