

## GenFast™ 3" MAX Seam Plate

ITEM NUMBER: 51006

### Description:

GenFast™ 3" (76 mm) MAX Seam Plate is a round, metal, barbed seam plate to be used with the GenFast #16 MAX Fastener. The eyehooks are unique grips that hold the membrane with minimal tearing. GenFast 3" (76 mm) MAX Seam Plate has an extruded center hole for increased pull through resistance.



GenFlex GenFast 3" (76 mm) MAX Seam Plates may be used to secure GenFlex TPO membrane to the roof deck in GenFlex TPO. Please refer to current GenFlex TPO specifications and details for specific applications.

### Method of Application:

1. GenFlex Roofing Systems recommends the use of a 6.5 Amp (min.), 0-2,500 RPM (max.) Screw gun for installation of GenFlex GenFast 3" (76 mm) MAX Seam Plates and GenFast #16 MAX Fastener.
2. Check current GenFlex specifications for exceptions and/or changes.

### Storage:

- Fasteners should be protected from moisture and kept dry at all times.
- If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

### Precautions:

- Eye protection is recommended when installing fasteners and plates.
- Seam Plates are manufactured from galvanized metal. Precautions should be taken to avoid metal slivers, etc.
- Refer to Material Safety Data Sheet for further information.

### Compliance:

Post Consumer Recycled Content: 0%  
Pre Consumer Recycled Content: 0%

### Packaging:

Bucket:	500 Pieces
---------	------------

### Physical Properties:

	Minimum Performance
Metal:	AZ 55 Galvalume®
Diameter:	3" (76 mm)
Thickness:	20 Gauge (0.037")
Edges:	All edges are deburred

Please contact the GenFlex Technical Department at 800-443-4272.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*