

REGION			REGION	
TSM:			CSR:	
email:			email:	
Phone:			Phone:	
Fax:			Fax:	

GenFlex Polyiso Insulation Order Form

Sold To:		PO#		DATE	
Ship To:		DELIVERY DATE			
		24 HOUR CALL#			
		CONTACT NAME			
		SPECIAL INSTRUCTIONS			
Tapered Quote #		Quote Version			

GenFlex Flat Polyiso Insulation

All GenFlex Polyiso insulations have a polyisocyanurate foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi. 25 psi polyisocyanurate is also available for an up charge. Please contact your GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ UNITS	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet per Truckload
			1.00	48	1,536	768	36,864
			1.25	38	1,216	608	29,184
			1.50	32	1,024	512	24,576
			1.75	27	864	432	20,376
			2.00	24	768	384	18,432
			2.30	20	640	320	15,360
			2.50	19	608	304	14,592
			2.80	17	544	272	13,056
			3.00	16	512	256	12,288
			3.25	14	448	224	10,752
			3.50	13	416	208	9,984
			3.75	12	384	192	9,216
			4.00	12	384	192	9,216

GenFlex Tapered Polyiso Insulation

Quantity/ UNITS	4X4	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 4	Slope	Max-Min Height Per Panel
		AA	64	1,024	1/8" Slope	0.5" - 1.0"
		A	38	608	1/8" Slope	1.0" - 1.5"
		B	26	416	1/8" Slope	1.5" - 2.0"
		C	20	320	1/8" Slope	2.0" - 2.5"
		G	32	512	1/4" Slope	1.0" - 2.0"
		H	18	288	1/4" Slope	2.0" - 3.0"
		X	48	768	1/4" Slope	.0.5" - 1.5"
		Y	24	384	1/4" Slope	1.5" - 2.5"
		Q	32	512	1/2" Slope	.0.5" - 2.5"

GenFlex Polyiso Cover Boards

GenFlex 1/2" standard iso cover board has a foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi, but 25 psi is also available for an upcharge. GenFlex 1/2" HD ISO cover board has a high density foam core with coated glass facers top and bottom. The standard compressive strength is 120 psi. Contact GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ UNITS	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet Per Truckload
			HD 1/2"	46	1,472	736	70,656
			Standard 1/2"	96	3,072	1536	73,728

The most commonly used tapered panels are listed here. GenFlex Tapered Polyiso is available in 1/3", 1/4", 1/8", 1/16" and 3/16" slopes per foot and in 4' x 4' panels. For more information please contact your GenFlex Territory Sales Manager.