



250 West 96th Street, Suite 150
 Indianapolis, IN 46260
 (800) 443-4272
www.genflex.com

Customer Service Fax:
 (317) 853-4601 or (877) 777-2909

Effective May 1, 2010
 Supersedes May 1, 2007

GenFlex Polyiso Insulation				
All GenFlex Polyiso insulations have a polyisocyanurate foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi, but 25 psi is also available for an upcharge. Contact GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.				
Thickness (Inches)	Pieces Per Bundle	Square Feet Per Bundle (4x8)	Square Feet Per Bundle (4x4)	Square Feet Per Truckload
1.00	48	1,536	768	36,864
1.25	38	1,216	608	29,184
1.50	32	1,024	512	24,576
1.75	27	864	432	20,376
2.00	24	768	384	18,432
2.30	20	640	320	15,360
2.50	19	608	304	14,592
2.80	17	544	272	13,056
3.00	16	512	256	12,288
3.25	14	448	224	10,752
3.50	13	416	208	9,984
3.75	12	384	192	9,216
4.00	12	384	192	9,216

GenFlex Tapered Polyiso Insulation				
Panel Code	Pieces Per Bundle	Square Feet Per Bundle (4x4)	Slope	Min - Max Thickness Per Panel
AA	64	1,024	1/8" Slope	0.5" - 1.0"
A	38	608	1/8" Slope	1.0" - 1.5"
B	26	416	1/8" Slope	1.5" - 2.0"
C	20	320	1/8" Slope	2.0" - 2.5"
G	32	512	1/4" Slope	1.0" - 2.0"
H	18	288	1/4" Slope	2.0" - 3.0"
X	48	768	1/4" Slope	0.5" - 1.5"
Y	24	384	1/4" Slope	1.5" - 2.5"
Q	32	512	1/2" Slope	0.5" - 2.5"

GenFlex Polyiso Cover Boards				
GenFlex 1/2" standard iso cover board has a foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi, but 25 psi is also available for an upcharge. GenFlex 1/2" HD ISO cover board has a high density foam core with coated glass facers top and bottom. The standard compressive strength is 120 psi. Contact GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.				
Thickness (Inches)	Pieces Per Bundle	Square Feet Per Bundle (4x8)	Square Feet Per Bundle (4x4)	Square Feet Per Truckload
0.50	96	3,072	1,536	73,728

Notes:

For specifics regarding freight and shipping, consult **GenFlex Domestic U.S. Freight Policy**.

The most commonly used tapered panels are listed here. GenFlex Tapered Polyiso is available in 1/2", 1/16" and 3/16" slopes per foot and in 4' x 4' panels. For more information, tapered system quotes or design assistance, please contact GenFlex Territory Sales Manager, Customer Service Representative or Estimating Services direct at (800) 443-4272, Extension 57212.

GenFlex Polyiso Plant Locations: Colorado, Connecticut, Florida, Kentucky, Pennsylvania, Texas, Wisconsin, and Utah.