



250 West 96th Street, Suite 150, Indianapolis, IN 46260
 800-443-4272 • www.genflex.com

PRODUCT DATA SHEET

GenFast™ GypTec Seam Plate

DESCRIPTION

GenFast™ GypTec Seam Plates are specifically designed to be used with GenFast™ GypTec Fasteners for attaching GenFlex membranes to approved decks, including cementitious wood fiber (i.e. Tectum) or gypsum.

PHYSICAL PROPERTIES

PROPERTY	MINIMUM PERFORMANCE
Material	Galvalume®
Material Thickness	0.030" (0.76 mm)
Corrosion Coating	AZ – 55; Exceeds FM 4470 Criteria
Plate Shape	2" (50.8 mm) Round

Galvalume is a registered trademark of BIEC International, Inc.

INSTALLATION

Position seam plates over the membrane as specified by GenFlex Specifications and Details. Attach the plates through the membrane and into the roof deck, using GenFast GypTec Fasteners. Install the plates with the "GenFlex" name showing.

Pullout Values - Results will vary depending on condition of deck. Verify pullout by onsite testing with a minimum 1.5" (38.1 mm) penetration into the deck. Check current GenFlex specifications for exceptions and/or changes.

INSTALLATION PRECAUTIONS

Eye protection must be worn during installation of the fasteners to prevent injury.

Care should be used when handling and/or transporting buckets of fasteners or plates.

Insulation plates are manufactured from Galvalume metal. Precautions should be taken to avoid metal slivers when handling and during installation.

Overdriving the fastener can cause damage to the insulation facer.

Fasteners should never penetrate through the underside of the deck



PRODUCT DATA

PRODUCT #	QUANTITY
W590051015	1,000 per bucket

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%

STORAGE

Plates should be stored in unopened containers protected from the weather at all times. If stored out of doors, place on skids in a dry area, and cover with a breathable tarp.

SHELF LIFE

Not applicable.

PRECAUTIONARY DATA

Refer to Material Safety Data Sheet for additional information.