



NOTE:

1. REFER TO GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. WATERTIGHT INTEGRITY OF THE WALL AND COPING MUST BE MAINTAINED BY OTHERS.
3. COPING STONE ATTACHMENT IS THE RESPONSIBILITY OF THE SPECIFIED CONTRACTOR.
4. ANCHOR BOLT SECUREMENT LUG MUST BE INSTALLED IN ACCORDANCE WITH MASONRY STANDARDS AND LOCAL BUILDING CODES.
5. GENFLEX EZ EPDM P&S MEMBRANE EXTENDING TO FACE OF WALL.
6. CONTINUOUS BEAD OF GENFLEX WATERSTOP ALONG ENTIRE EDGE OF EZ EPDM P&S AND WALL. WATERSTOP ALSO APPLIED AROUND ANCHOR.
7. APPROVED PRIMERS INCLUDE GENPRIME AND ALL PURPOSE LVOC PRIMER.
8. APPROVED PRIMER REQUIRED ON ALL VERTICAL SURFACES.

USE APPROPRIATE BASE TIE-IN



TERMINATION AT TOP OF WALL WITH COPING

ACCEPTABLE SYSTEMS: EZ EPDM PEEL & STICK™ SELF ADHERED

(800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

07/28/2023

NOT TO SCALE

DETAIL NO.

EZE-PS-T-03