

Product Data Sheet

GENFAST™ TERMINATION BAR



Description

GenFast™ Termination Bar is a corrosion resistant aluminum material used for terminating and sealing membrane wall flashings to various approved substrates as outlined by current GenFlex Specifications and Details.



Physical Properties

PROPERTY	MINIMUM PERFORMANCE
Material	Corrosion Resistant Aluminum
Thickness	0.090" (2.3 mm)
Features	GenFlex logo on each section Reservoir channel for Termination Caulk on top
Holes	Pre-punched 0.28" x 0.38" (7 x 10 mm) Slotted Holes 3.93" (100 mm) O.C.

Installation

1. Substrates must be free from dust, dirt, oil, water, and other contaminants (wall areas above termination bar must not pass water). Install per current GenFlex specifications.
2. Apply GenFlex Waterstop behind flashing membrane.
3. Install flat side of bar towards flashing so "lip" is facing upwards, and forms a wide reservoir for edge caulk.
4. Anchor bar through pre-punched holes at a rate to maintain a seal to the wall against waterstop. (Max. 12" o.c. (304.8mm)).
5. Remove excess flashing material above bottom of lap sealant reservoir channel.
6. Install GenFlex Termination Caulk into reservoir channel.
7. Consult GenFlex Roofing Systems specifications for specifics.

Application Precautions

1. Do not use as a bar anchor.
2. Where field cutting is necessary, remove any burrs from bar.
3. Clean up shavings, etc., that may occur from field cutting.
4. Install flat side of bar towards flashing so "lip" is facing upwards, and forms a wide reservoir for edge caulk.
5. Keep a space of ¼" (6mm) between each length of GenFlex Termination Bar.
6. GenFlex Termination Bars must be installed directly to the wall surface, not existing sheet metal, flashings, etc.
7. Install GenFlex Termination Bar on hard, smooth surfaces only. Do not install on substrates where seal is lost at mortar joints, etc.
8. Install GenFlex Termination Bar vertically where base flashing(s) end.
9. Do not install GenFlex Termination Bar to wood or other porous surfaces.
10. At inside and outside corners, GenFlex Termination Bar must be cut and continued.
11. GenFlex Termination Bar must be fastened a maximum of 1" (25 mm) from each end of all sections.

Product Data Sheet

GENFAST™ TERMINATION BAR



Product Data

SIZE	CONTENTS	ITEM #
1.25" (32 mm) X 10' (3 m)	50 Bars per Tube	W590010088
1.25" (32 mm) X 5' (1.5 m)	50 Bars per Tube	W590051239

LEED Information

Recycled Content

Post Consumer	0%
Post Industrial	0%

Storage

Termination Bar should be protected from moisture and kept dry at all times. If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Shelf Life

Not applicable

Precautionary Data

Eye protection is recommended when installing the appropriate fastener through the Termination Bar.

Refer to Material Safety Data Sheet for additional information.