

## GENFAST™ POLYMER BATTEN STRIP

### Item Description

POLYMER BATTEN STRIP

### Item Number

W590051005



## Product Information

### Description

GenFast Polymer Batten Strip is to be used for the mechanical attachment of the membrane at the perimeter of the building, around certain penetrations, and for all mechanically attached GenFlex roofing systems. Since the GenFlex GenFast Polymer Batten Strip is a substitute for GenFlex Metal Anchor Bars in many applications, consult the appropriate GenFlex specification for specific installation procedures.

### Typical Properties

Property	Typical Values
Length	250' (76.2 m) coil
Width	1" (25.4 mm)
Thickness	1/20" (1.27 mm)
Holes	Pre-punched 6" (152.4 mm) o.c.
Continuous Use Temperature	-50 °F to +212 °F (-45.6 °C to 100 °C)
Ultimate Tensile Strength, minimum	35,000 psi (241 MPa)

### Installation

1. Substrate must be free from dust, dirt, oil, water, or other contaminants.
2. Install polymer batten strip in a straight line by anchoring one end and stretching out 20 feet and anchoring again.
3. Set the fastener head flush with the Polymer Batten Strip so that the strip shows only a slight depression around the fastener head.
4. Overlap ends 1". All cut ends must be rounded.
5. Fastener placement may be varied by moving the fastener at least 2" from the hole that did not properly engage the deck. Set the fastener in the center of the strip. Drive the fastener as described above fully engaging the deck.

### Installation Precautions

1. Overdriving causes the Polymer Batten Strip to kink.
2. All cut ends must be rounded.

### Packaging

250 LF (76.2 m) per carton

### \*LEED® Information

Post-Consumer Recycled Content: 0%

Post-Industrial Recycled Content: 0%

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

## Storage

Fasteners should be protected from moisture and kept dry at all times. If stored outdoors, place on skids in a dry area and cover with a breathable tarp.

## Precautionary Data

- Eye protection is recommended when installing fasteners and plates.
- Refer to Safety Data Sheet for additional information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*