

## GENPOCKET T

### Item Description

Pocket & Ring

### Color

White

Grey

Tan

### Item Number

W590030260N

W5900G026N

W5900T026N



## Product Information

### Description

GenFlex GenPocket T is a penetration pocket vacuum formed, ensuring uniform product quality and consistency. Each GenPocket T is designed for use with GenFlex TPO membranes.

**NOTE:** Primer shown in photo but not supplied with the penetration pocket. Primer and pourable sealer must be ordered separately.

### Typical Properties – Penetration Pocket

Property	Typical Values
Color	White
Base	Vacuum formed TPO
Size	6" (152 mm) inside diameter, 0.045" (1.1 mm) thick with 12.12" (307.8 mm) flange diameter
Coverage	Fits up to 3½" (90 mm) diameter penetration or penetration cluster

### Typical Properties – Plastic Ring

Property	Typical Values
Color	White
Base	Schedule 40 PVC
Shape	Round pre-cut in one place
Size	6.67" (169 mm) outside diameter, with a .32" (8.1 mm) wall, 2" (51 mm) high

## Installation

Refer to current GenFlex Technical Specifications for additional instructions.

1. Remove existing flashing materials, rust, dirt, etc., from penetration prior to installing the GenPocket T.
2. Seal around the penetration prior to installation to prevent Pourable Sealer from flowing into the roof system and possibly into the building.
3. Open the PVC ring and place around the penetration.
4. If required, cut the penetration pocket through the flange and side in one place and install it over the PVC ring so that the ring fits completely inside the top overhang of the pocket.
5. If cut in #4, then cut a piece of TPO flashing long enough to cover the cut in the pocket and the membrane. Heat weld the flashing on the vertical cut in the pocket and to the lip in the cavity.
6. Center the pocket around the penetration and weld the flange to the membrane. Next, if needed, weld the flashing onto the flange and cut membrane. Weld and roll the flange step-off thoroughly.
7. After the weld cools, apply the PTO Clear Primer with the dauber to all areas of the penetration and all surfaces that the Pourable Sealer will contact within the cavity. Make sure the top of the pocket is primed also.
8. Allow the primer to dry and then mix and add Pourable Sealer, being careful to mound it from the penetration to the top of the pocket to shed water away from the penetration.

**Product Data****GENPOCKET T - SIZE**

6" (152 mm) inside diameter,  
0.045" (1.1 mm) thick with 12.12" (307.8 mm) flange diameter

**KIT CONTAINS**

6 TPO penetration pockets,  
6 Plastic Rings

**\*LEED® Information****Recycled Content**

Post Consumer 0%

Post Industrial 0%

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

**Storage**

- Store in original unopened container indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C). When exposed to lower temperatures, restore to room temperature prior to use.
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

**Shelf Life**

12 months; shelf life will be shortened if exposed to elevated temperatures.

**Precautionary Data**

- For professional use only.
- To avoid sources of punctures and physical damage, take care when moving, transporting, or handling.
- Contact GenFlex Roofing Systems Technical Department
- Refer to Safety Data Sheet prior to use.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*