

# **GenFlex Scrub Pads and Handles**

**Item Description** 

**Item Number** 

Molded Plastic Handle and Scrub Pads

W590030052



### **Product Information**

## **Description**

GenFlex Scrub Pads and Handles consist of abrasive scrub pads and molded plastic handles. The plastic handle is designed to hold the scrub pad during the application of GenFlex primers to EPDM and TPO roofing membranes.

Typical Properties – Scrub Pad	
Property	Typical Values
Material	Solvent resistant nylon fibers – abrasive fiber (240 grit)
Color	Dark Grey
Dimensions	3" x 5" (76.2 mm x 127 mm)
Packaging	30 Scrub Pads per Carton

Typical Properties – Ha	andle
Property	Typical Values
Material	Molded Polyethylene with micro fastening system
Color	Tan
Packaging	4 Handles per Carton

### **Application**

Please refer to current GenFlex EPDM and TPO specifications and details for specific information.

- 1. Place the abrasive Scrub Pad on the bottom of the handle with positive pressure working the pad fibers into the micro fasteners. This will keep the Scrub Pad in contact with the handle during primer application.
- 2. After saturating the pad with primer, use continuous back and forth scrubbing stroked with forceful pressure to apply the primer to the membrane splicing area. Proper application will result in a membrane surface covered with primer with no streaks or puddles.
- 3. Each Scrub Pad is designed to prime approximately 100 200 feet of a 6" wide area. Pads should be changed regularly to improve both application and performance of the primer.



#### \*LEED® Information

Recycled Content

Post Consumer 0% Post Industrial 0%

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

## **Storage**

- Store in original unopened container indoors at temperatures between 60F (16 °C) and 80F (27 °C). Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C). When exposed to lower temperatures, restore to room temperature prior to use.
- Do not store in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

## **Precautionary Data**

Take care when moving, transporting, and handling to avoid sources of physical damage.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.