

TPO WALKWAY PAD

Item Description

30" X 50' (.76 m to 15.24 m)

Item Number

W590030000



Product Information

Description

The GenFlex TPO Walkway Pad is a reinforced walkway composed of thermoplastic material. The pad is produced into 30" (0.76 m) wide by 50' (15 m) long rolls. The pad has a textured surface and a smooth bottom surface for easy welding to TPO roof membrane.

The walkway pad or acceptable paver is recommended in areas where necessary rooftop traffic will occur to help protect the roofing system from unnecessary damage as follows:

- At all access points (ladders, hatches, doorways, etc.) to the roof.
- As a walkway system on roofs subjected to traffic more frequently than once per month.
- Around rooftop equipment that requires periodic maintenance.

Method of Application

1. Ensure the membrane surface is clean, completely dry and free of debris.
2. Place the TPO Walkway Pad over the TPO membrane with the textured side up. Cut the material into lengths that can be easily handled. After cutting, allow walkway pad to relax before installation.
3. The TPO Walkway Pad should be installed in 10' (3 m) long sections with a space between each section to allow for proper drainage. Lay the pad out so that it does not result in ponding water.
4. Do not apply walkway pad over TPO membrane seams.
5. Walkway pads may be installed by heat welding the perimeters of each TPO Walkway Pad section to the TPO roof membrane. To achieve the best aesthetic quality, weld when ambient temperature is between 60 °F - 80 °F (15.6 °C -27 °C). Welder temperature settings will vary with the ambient conditions
6. Exposed reinforcement requires an application of cut edge sealant.

Typical Properties		
Property	ASTM Standard	Typical Value
Overall Thickness	D 751	0.156" ± 0.010" (3.96 mm – .254 mm)
Elongation at Break	D 421	300%
Linear Dimensional Stability	D 12004	0 ± 0.5%
Accelerated Weathering	G 155	5000 hours, 10 x magnification, no cracks

Precautionary Data

Refer to current GenFlex Technical Specifications for additional instructions.

- Do not expose walkway material to any open flames or ignition sources
- Refer to the Safety Data Sheet for further information.

*LEED® Information

Recycled Content

Post Consumer 0%

Post Industrial 0%

Manufacturing Location: Wellford, SC

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

- Store away from sources of punctures and physical damage.
- Assure that structural decking will support the loads incurred by material when stored on rooftop. The deck load limitations should be specified by the project designer.
- Store away from ignition sources as membrane will burn when exposed to open flame.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.