Safety Data Sheet

GenFlex Roofing Systems

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier	
Product Name	 EPDM Edge Caulk LVOC
1.2 Relevant identified u	ses of the substance or mixture and uses advised against
Relevant identified use(s)	Construction
1.3 Details of the supplie	er of the safety data sheet
Manufacturer	Firestone Building Products Company
	250 West 96th Street Indianapolis, IN 46260 United States
	genflexmsds@bfdp.com
Telephone (Genera	I) • 800-428-4442
1.4 Emergency telephor	ne number
Manufacturer	• (800) 424-9300 - CHEMTREC

.			
Manufacturer	•	(703) 527-3887 - CHEMTREC - Internationa	зI

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

2.1 Classification of the substance or mixture

|--|

Skin Irritation 2 - H315 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336 Carcinogenicity 1A - H350

2.2 Label Elements

CLP

DANGER



Hazard statements · H315 - Causes skin irritation

- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H350 May cause cancer.

Precautionary statements

- P202 Do not handle until all safety precautions have been read and understood.
 - P261 Avoid breathing dust.
 - P264 Wash thoroughly after handling.

	P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves . P281 - Use personal protective equipment as required.
Response •	 P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P321 - Specific treatment, see supplemental first aid information. P362 - Take off contaminated clothing and wash before reuse. P332+P313 - If skin irritation occurs: Get medical advice/attention. P308+P313 - IF exposed or concerned: Get medical advice/attention.
Storage/Disposal •	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
2.3 Other Hazards	
CLP ·	According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

 Skin Irritation 2 Eye Irritation 2 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects Carcinogenicity 1A

2.2 Label elements OSHA HCS 2012



Hazard statements • Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness May cause cancer.

Precautionary statements

Prevention •	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response •	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If on skin: Wash with plenty of water . Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Storage/Disposal	Store in a well-ventilated place. Keep container tightly closed. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
2.3 Other hazards	
OSHA HCS 2012	Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.
Canada According to: WHMIS	
2.1 Classification of the su	ibstance or mixture
WHMIS	Other Toxic Effects - D2A Other Toxic Effects - D2B
2.2 Label elements	
WHMIS	\sim

WHMIS

Other Toxic Effects - D2A

Other Toxic Effects - D2B

2.3 Other hazards WHMIS

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

٠

3.1 Substances

· Material does not meet the criteria of a substance.

3.2 Mixtures

			Compos	ition	
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Limestone	CAS:1317-65- 3 EC Number:215- 279-6	50% TO 100%	NDA	EU CLP: STOT RE 2 (Lung, Inhl), H373 OSHA HCS 2012: STOT RE 2 (Lung, Inhl)	NDA
Light aliphatic solvent naphtha	CAS:64742-89 -8 EC Number:265- 192-2 EU Index:649- 267-00-0	5% TO 20%	NDA	EU CLP: Annex VI, Table 3.1: Skin Irrit. 2, H315; Asp Tox. 1, H304; STOT SE 3: Narc., H336; Aquatic Chronic 2, H411; Flam. Liq. 3, H226 OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2; Skin Irrit. 2; Asp. Tox. 1; STOT SE: Narc. & Resp. Irrit.	NDA
	CAS:64742-52				

Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	-5 EC Number:265- 155-0 EU Index:649- 465-00-7	2.5% TO 10%	Ingestion/Oral- Rat LD50 • >5000 mg/kg Skin-Rabbit LD50 • >2000 mg/kg	EU CLP: Annex VI, Table 3.1: Carc. 1B, H350 OSHA HCS 2012: Skin Irrit. 2	Contains less than 3% DMSO. Carcinogen classification not applicable.
Quaternary ammonium compounds, bis (hydrogenated tallow alkyl)dimethyl-, salt with bentonite	CAS:68953-58 -2 EC Number:273- 219-4	<= 2.5%	NDA	EU CLP: Not Classified OSHA HCS 2012: Not Classified	NDA
Carbon Black	CAS: 1333-86- 4 EC Number: 215- 609-9	<= 2.5%	Ingestion/Oral- Rat LD50 • >15400 mg/kg Skin-Rabbit LD50 • >3 g/kg	EU CLP: Carc. 2, H351; STOT RE 1, H372 OSHA HCS 2012: Carc. 2; STOT RE 1 (Lungs, Inhl); Comb. Dust	NDA
Stearic acid	CAS: 57-11-4 EC Number: 200- 313-4	<= 1%	Skin-Rabbit LD50 • >5 g/kg Ingestion/Oral-Rat LD50 • 4600 mg/kg	EU CLP: Skin Irrit. 2, H315 OSHA HCS 2012: Skin Irrit. 2	NDA
Calcium oxide	CAS: 1305-78- 8 EC Number: 215- 138-9	<= 1%	NDA	EU CLP: Skin Corr. 1C, H314; Eye Dam. 1, H318 OSHA HCS 2012: Skin Corr. 1C; Eye Dam. 1	NDA
Quartz	CAS:14808-60 -7 EC Number:238- 878-4	<= 0.5%	NDA	EU CLP: Carc. 1A, H350i; STOT RE 1, H372 (Lungs, Inhl) OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs, Inhl)	NDA

See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation	 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Do not use mouth-to-mouth method if victim inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if artificial oxygen is administered.
Skin	 IF ON SKIN: Wash with plenty of soap and water. Remove and isolate contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Еуе	 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
Ingestion	 Do NOT induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Get medical attention immediately.
4.2 Most important syn	nptoms and effects, both acute and delayed
	Defer to Section 11. Toxicological Information

• Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Media

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Unsuitable Extinguishing • No data available.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards	Containers may explode when heated.
Hazardous Combustion Products	No data available
FOAd to far fireficietory	

5.3 Advice for firefighters

 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
 Wear positive pressure self-contained breathing apparatus (SCBA).
 Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Emergency Procedures 6.2 Environmental preca	Stay upwind. Keep out of low areas. Keep unauthorized personnel away.
Personal Precautions	 Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

· Avoid run off to waterways and sewers.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up
Measures• Stop leak if you can do it without risk.
Carefully shovel or sweep up spilled material and place in suitable container.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

- Handling
- Use only with adequate ventilation. Wear appropriate personal protective equipment. Avoid breathing dust. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Keep container closed when not in use. Store in a cool location away from direct heat. Keep away from incompatible materials.

7.3 Specific end use(s)

• Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

				Expo	sure Limits	/Guideline	s		
	Resu	It	ACGIH	Canad	da Alberta	Canada B Colum		Canada Manito	ba Canada New Brunswick
Quartz (14808-60-7)	TWAs		0.025 mg/m3 TWA (respirable fraction)		g/m3 TWA ble te)	0.025 mg/m3 TWA (respirable)		0.025 mg/m3 TWA (respirable fractio	
Calcium oxide (1305-78-8)	TWA	s 2 mg	g/m3 TWA	2 mg/m3	TWA	2 mg/m3 TW/	Ą	2 mg/m3 TWA	2 mg/m3 TWA
Carbon Black (1333-86-4)	TWA		g/m3 TWA alable fraction)	3.5 mg/m	ו3 TWA	3 mg/m3 TWA (inhalable)	Ą	3 mg/m3 TWA (inhalable fraction) 3.5 mg/m3 TWA
Limestone (1317-65-3)	TWAs	s Not	established	10 mg/m	3 TWA	10 mg/m3 TWA (total dust); 3 mg/m3 TWA (respirable fraction)		Not established	10 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica)
	STEL	s Not	established	Not estal	blished	20 mg/m3 ST dust)	EL (total	Not established	Not established
	-		E	cposure	Limits/Gu	idelines (C	on't.)	-	
	Resu	1 + 1	nada Northwest Territories	Canada	Nova Scotia	Canada Nu	unavut	Canada Ontari	o Canada Quebec
Quartz (14808-60-7)	TWAs	(res	n3 TWA (total		5 mg/m3 TWA irable fraction) 0.1 mg/m3 TV 0.3 mg/m3 TV mass)		iass);	0.10 mg/m3 TWA (designated substances regulation, respira listed under Silica, crystalline)	
Calcium oxide	STEL	s 4 mg	J/m3 STEL	Not established		4 mg/m3 STEL		Not established	Not established
(1305-78-8)	TWAs	s 2 mg/m3 TWA		2 mg/m3 TWA		2 mg/m3 TWA		2 mg/m3 TWA	2 mg/m3 TWAEV
Carbon Black	STEL	s 7 mg	J/m3 STEL	Not established		7 mg/m3 STEL		Not established	Not established
(1333-86-4)	TWA	s 3.5 r	ng/m3 TWA	3 mg/m3 TWA (inhalable fraction)		3.5 mg/m3 TWA		3 mg/m3 TWA (inhalable)	3.5 mg/m3 TWAEV
Limestone TWAs (1317-65-3)		(res	g/m3 TWA birable mass); 10 n3 TWA (total s)	Not estal	blished	5 mg/m3 TW/ (respirable m mg/m3 TWA mass)	ass); 10	Not established	10 mg/m3 TWAEV (Limestone, containing no Asbestos and <1% Crystalline silica, total dust)
			й ⁻		8	idelines (C	on't.)		
	F	lesult	Canada Saskat	chewan	Canada	a Yukon		NIOSH	OSHA
Quartz (14808-60-7)	т	WAs	0.05 mg/m3 TWA (respirable fraction under Silica - cryst		300 particle/r (listed under		0.05 mg/m3 TWA (respirable dust)		Not established
Calcium oxide	Т	WAs	2 mg/m3 TWA		<u> </u>		2 mg/m3 TWA 5 n		5 mg/m3 TWA
(1305-78-8)	S	TELs	Not established		4 mg/m3 STE	L	Not esta	blished	Not established
Carbon Black (1333-86-4)	Т	WAs	3.5 mg/m3 TWA		3.5 mg/m3 T\	mg/m3 T WA black in Polycycl		n3 TWA; 0.1 WA (Carbon presence of ic aromatic rbons, as PAH)	3.5 mg/m3 TWA
			Not established		7 mg/m3 STEL Not es				

Limestone (1317-65-3)	TWAs	10 ma/m + 100 ma/m	30 mppcf 1 WA; 10 mg/m3	0	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
	STELs	Not established	20 mg/m3 STEL	Not established	Not established

Exposure Control Notations

Canada Ontario

•Quartz (14808-60-7): **Designated Substances:** (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline)) **Canada Quebec**

•Quartz (14808-60-7): Carcinogens: (C2 carcinogen - effect suspected in humans)

ACGIH

•Carbon Black (1333-86-4): Carcinogens: (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)

•Quartz (14808-60-7): Carcinogens: (A2 - Suspected Human Carcinogen)

Exposure Limits Supplemental OSHA

•Quartz (14808-60-7): Mineral Dusts: ((30)/(%SiO2 + 2) mg/m3 TWA, total dust; (250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

ACGIH

•Carbon Black (1333-86-4): TLV Basis - Critical Effects: (bronchitis)

•Calcium oxide (1305-78-8): TLV Basis - Critical Effects: (upper respiratory tract irritation)

•Quartz (14808-60-7): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

8.2 Exposure controls

Engineering Measures/Controls	ventilation sh applicable, u controls to m	ial is designed to be used outdoors, in roofing applications. Good general should be used. Ventilation rates should be matched to conditions. If use process enclosures, local exhaust ventilation, or other engineering maintain airborne levels below recommended exposure limits. If exposure not been established, maintain airborne levels to an acceptable level.				
Personal Protective Equipme	ent					
Respiratory	Standard EN	OSHA respirator regulations found in 29 CFR 1910.134 or European EN 149. Use a NIOSH or European Standard EN 149 approved respirator if imits are exceeded or symptoms are experienced.				
Eye/Face	 Wear protect 	ective eyewear (goggles, face shield, or safety glasses).				
Skin/Body	 Wear approp 	priate gloves.				
Environmental Exposure Controls	 In case of sp waste produce 	spills, keep product clear of sewers, waterways or land areas. Dispose of Juct in accordance with national and local laws and regulations.				
Key to abbreviations						
ACGIH = American Conference of Gove Industrial Hygiene		TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)				
NIOSH = National Institute of Occupati Health		TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures				
OSHA = Occupational Safety and Hea Administration		TWAEV = Time-Weighted Average Exposure Value				
STEL = Short Term Exposure Limits a minute exposures	re based on 15-					

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description

Physical Form	Liquid (Paste)	Appearance/Description	Black paste with a petrol-like odor.

Color	Black	Odor	Petrol-like
Odor Threshold	Data lacking		
General Properties	-		
Boiling Point	Data lacking	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	рН	Data lacking
Specific Gravity/Relative Density	Data lacking	Bulk Density	1.35 g/cm ³
Water Solubility	Insoluble	Viscosity	> 20.5 Centistoke (cSt, cS) or mm2/sec
Explosive Properties	Data lacking	Oxidizing Properties:	Data lacking
Volatility	•		•
Vapor Pressure	45 mmHg (torr) @ 20 °C(68 °F)	Vapor Density	3.8 Air=1
Evaporation Rate	9.2 n-Butyl Acetate = 1	VOC (Vol.)	< 250 g/L
Flammability			
Flash Point	83 °C(181.4 °F)	UEL	6.7 %
LEL	0.9 %	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental	-	-	
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

• No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

• No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

• Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

Excess heat.

10.5 Incompatible materials

· Oxidizing agents.

10.6 Hazardous decomposition products

None known.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components							
(netroleum) (Highly		Irritation: Skin-Rabbit • 500 mg • Severe irritation					
		Acute Toxicity: Ingestion/Oral-Rat LD50 • >15400 mg/kg; Behavioral:Somnolence (general depressed					

Carbon Black (<= 2.5%)	ck (<= 1333- 86-4 Aution-Rat • 50 g/L 13 Week(s); DNA damage • Inhalation-Rat • 50 μg/L 13 Week(s)-Intermittent; DNA damage • Inhalation-Rat • 50 μg/L 13 Week(s)-Intermittent; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 11600 μg/m ³ 18 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:</i> Carcinogenic by RTECS criteria; <i>Lungs, Thorax, or Respiration:</i> Tumors			
Stearic acid (<= 1%)	57-11- 4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4600 mg/kg; Skin-Rabbit LD50 • >5 g/kg; Irritation: Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Mutagen: DNA damage • Unreported Route-Human • Liver (Somatic cell) • 10 mg/L 20 Hour(s); Tumorigen / Carcinogen: Implant-Mouse TDLo • 400 mg/kg; <i>Tumorigenic</i> :Equivocal tumorigenic agent by RTECS criteria; <i>Kidney, Ureter, and Bladder</i> :Tumors		
Quartz (<= 0.5%)	14808 -60-7	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; <i>Lungs, Thorax, or</i> <i>Respiration</i> :Fibrosis, focal (pneumoconiosis); <i>Lungs, Thorax, or Respiration</i> :Cough; <i>Lungs, Thorax, or</i> <i>Respiration</i> :Dyspnea; Inhalation-Rat TCLo • 200 mg/kg; <i>Lungs, Thorax, or Respiration</i> :Fibrosis, focal (pneumoconiosis); <i>Lungs, Thorax, or Respiration</i> :Other changes; <i>Nutritional and Gross Metabolic</i> :Changes <i>in Chemistry or Temperature</i> :Fe; Intratracheal-Mouse TDLo • 80 mg/kg; <i>Lungs, Thorax, or Respiration</i> :Fibrosis (interstitial); <i>Immunological Including Allergic</i> :Increase in cellular immune response; <i>Biochemical:Metabolism (intermediary)</i> :Effect on inflammation or mediation of inflammation; Multi-dose Toxicity: Inhalation-Hamster TCLo • 3 mg/m³ 6 Hour(s) 78 Week(s)-Intermittent; <i>Lungs, Thorax, or</i> <i>Respiration</i> :Fibrosis (interstitial); <i>Lungs, Thorax, or Respiration</i> :Changes in lung weight; Inhalation-Rat TCLo • 6.2 mg/m³ 6 Hour(s) 6 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration</i> :Other changes; <i>Blood</i> :Changes in spleen; <i>Immunological Including Allergic</i> :Increase in cellular immune response; Mutagen: Micronucleus test • Unreported Route-Hamster • Lung (Somatic cell) • 160 µg/cm³; DNA damage • Unreported Route-Human • Other Cell Type • 120 mg/L 24 Hour(s); Micronucleus test • Unreported Route-Human • Lung (Somatic cell) • 40 µg/cm³; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s) 71 Week(s)-Intermittent; <i>Tumorigenic</i> :Carcinogenic by RTECS criteria; <i>Liver</i> :Tumors		

GHS Properties	Classification
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Data lacking OSHA HCS 2012 • Eye Irritation 2
Skin sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Respiratory sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Carcinogenicity 1A OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation

STOT-RE	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Potential Health Effects Inhalation	
Acute (Immediate)	 May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
Chronic (Delayed)	No data available.
Skin	
Acute (Immediate)	Causes skin irritation.
Chronic (Delayed)	No data available.
Еуе	
Acute (Immediate)	Causes serious eye irritation.
Chronic (Delayed)	No data available.
Ingestion	
Acute (Immediate)	Ingestion of this product unlikely.
Chronic (Delayed)	No data available.
Carcinogenic Effects	 Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Carcinogenic Effects

	CAS	IARC	NTP				
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen				
Carbon Black	1333-86-4	Group 2B-Possible Carcinogen	Not Listed				

Key to abbreviations

LD = Lethal Dose TC = Toxic Concentration TD = Toxic Dose

Section 12 - Ecological Information

12.1 Toxicity

Material data lacking.

12.2 Persistence and degradability

• Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.
- 12.4 Mobility in Soil
- Material data lacking.

12.5 Results of PBT and vPvB assessment

• No PBT and vPvB assessment has been conducted by the manufacturer.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not Regulated	NDA	NDA	NDA
ADN	NDA	Not Regulated	NDA	NDA	NDA
ADR/RID	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

14.6 Special precautions for • None specified. **user**

14.7 Transport in bulk • according to Annex II of MARPOL 73/78 and the IBC Code

Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic

	State Right To Know						
Component	CAS	MA	NJ	PA			
Calcium oxide	1305-78-8	Yes	Yes	Yes			
Carbon Black	1333-86-4	Yes	Yes	Yes			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	No	No	No			
Light aliphatic solvent naphtha	64742-89-8	No	No	No			
Limestone	1317-65-3	Yes	Yes	Yes			
Quartz	14808-60-7	Yes	Yes	Yes			
Quaternary ammonium compounds, bis (hydrogenated tallow alkyl)dimethyl	68953-58-2	No	No	No			

-, salt with bentonite				
Stearic acid	57-11-4	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Calcium oxide	1305-78-8	Yes	No	Yes	No	Yes
Carbon Black	1333-86-4	Yes	No	Yes	Yes	Yes
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Yes	No	Yes	No	Yes
Light aliphatic solvent naphtha	64742-89-8	Yes	No	Yes	No	Yes
Limestone	1317-65-3	No	Yes	Yes	No	Yes
Quartz	14808-60-7	Yes	No	Yes	No	Yes
Quaternary ammonium compounds, bis (hydrogenated tallow alkyl)dimethyl -, salt with bentonite	68953-58-2	Yes	No	Yes	No	Yes
Stearic acid	57-11-4	Yes	No	Yes	No	Yes

Canada

57-11-4 64742-52-5	Uncontrolled product according to WHMIS classification criteria
64742-52-5	
	Not Listed
1305-78-8	E
1333-86-4	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific
	Issues - Carbon Black, non- respirable on Health Canada's WHMIS Division website.)
1317-65-3	D2A
64742-89-8	B2
68953-58-2	Not Listed
14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specifi Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
	1317-65-3 64742-89-8 68953-58-2

Stearic acid	57-11-4	1 %
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	1 %
Carbon Black	1333-86-4	1 %
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
• Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	1 %
Environment Canada - CEPA - Priority Substances List		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
• Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with	68953-58-2	Not Listed

Quartz

Denmark

Environment Denmark - List of Undesirable Substances - Product Groups/Function		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed

14808-60-7

Not Listed

Europe

Other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Carc.Cat.2; R45
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed

• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	T R:45 S:53-45
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	T R:45-46-65 S:53-45
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	L
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Р
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
Stearic acid	57-11-4	Not Listed
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	S:53-45
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	S:53-45
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed

United States

.S OSHA - Process Safety Management - Highly Hazardous Chemicals		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
• Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with ntonite	68953-58-2	Not Listed
Quartz	14808-60-7	Not Listed
S OSHA - Specifically Regulated Chemicals		
Stearic acid	57-11-4	Not Listed

2-52-5	Not Listed
-78-8	Not Listed
-86-4	Not Listed
-65-3	Not Listed
2-89-8	Not Listed
3-58-2	Not Listed
8-60-7	Not Listed
1-4	Not Listed
2-52-5	Not Listed
-78-8	Not Listed
-86-4	Not Listed
-65-3	Not Listed
2-89-8	Not Listed
3 59 3	Not Listed
3-58-2	Not Listed
8-60-7	Not Listed
1-4	Not Listed
2-52-5	Not Listed
-78-8	Not Listed
-86-4	Not Listed
-65-3	Not Listed
2-89-8	Not Listed
3-58-2	Not Listed
8-60-7	Not Listed
1-4	Not Listed
2-52-5	Not Listed
-78-8	Not Listed
-86-4	Not Listed
-65-3	Not Listed
2-89-8	Not Listed
3-58-2	Not Listed
8-60-7	Not Listed
1-4	Not Listed
2-52-5	Not Listed
-78-8	Not Listed
-86-4	Not Listed
-65-3	Not Listed
2-89-8	Not Listed
3-58-2	Not Listed
8-60-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
 Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite 	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
 Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite 	68953-58-2	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)
U.S California - Proposition 65 - Developmental Toxicity		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed

Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
Stearic acid	57-11-4	Not Listed
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with	68953-58-2	Not Listed
bentonite Quartz	14808-60-7	Not Listed
		Hot Elotod
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Stearic acid	57-11-4	Not Listed
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with	68953-58-2	Not Listed
bentonite Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
Stearic acid	57-11-4	Not Listed
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	Not Listed
• Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed

United States - Pennsylvania

57-11-4	Not Listed	
64742-52-5	Not Listed	
1305-78-8	Not Listed	
	64742-52-5	64742-52-5 Not Listed

Carbon Black	1333-86-4	Not Listed
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
• Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed
U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
Stearic acid	57-11-4	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	64742-52-5	Not Listed
Calcium oxide	1305-78-8	Not Listed
Carbon Black	1333-86-4	
Limestone	1317-65-3	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl-, salt with bentonite	68953-58-2	Not Listed
• Quartz	14808-60-7	Not Listed

15.2 Chemical Safety Assessment

• No Chemical Safety Assessment has been carried out.

15.3 Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Relevant Phrases (code & full text)

	 H226 - Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage H350i - May cause cancer by inhalation. H351 - Suspected of causing cancer. H372 - Causes damage to organs through prolonged or repeated exposure. H373 - May cause damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects
	 R34 - Causes burns. R38 - Irritating to skin. R40 - Limited evidence of a carcinogenic effect. R41 - Risk of serious damage to eyes. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R48/23 - Toxic: danger of serious damage to health by prolonged exposure through inhalation. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed.
Revision Date	• 27/April/2016
Preparation Date	• 18/April/2012
Other Information	 Changes to this revision: Updated information throughout the SDS based upon further testing & evaluation of the product.
Disclaimer/Statement of Liability	 The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or

representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company, LLC assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No Data Available