

## CLEANER

**Item Description**  
1 GALLON (3.8 liter)

**Item Number**  
W590010092



## Product Information

### Description

GenFlex Cleaner is designed to clean GenFlex FlexWhite EPDM, EPDM and TPO membranes to be welded, or receive GenFlex Primers, Adhesives and Sealants. Substrates cleaned with GenFlex Cleaner to receive Peel & Stick products shall be further prepared by the application of the appropriate GenFlex Primer.

Typical Properties	
Property	Typical Values
Solvents	Naphthenic Solvents
Viscosity	Very thin, free flowing
Weight	6.25 ± .25 lb/gal (0.77 ± 0.05 kg/L)
V.O.C. Content	750 g/L

### Installation

1. Surfaces to be welded, or receive GenFlex Primers, Adhesives and Sealants shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminates using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with GenFlex Cleaner, in circular motions with heavy pressure over the affected areas. Membrane with caked dirt, including in-service TPO membrane, should be scrubbed using Scrub Pad & Handle wetted with GenFlex Cleaner, followed by cleaning with clean dry rags to remove contaminates.
3. Allow surfaces cleaned with GenFlex Cleaner to dry completely (usually within 10 to 30 minutes) before welding, or applying Primers, Adhesives and Sealants per GenFlex's current specifications and details.

### Product Data

1 gallon (3.8 liter), 4 per carton  
Coverage Rate: 200-250 ft<sup>2</sup>/gallon (4.9 -6.1 m<sup>2</sup>/L) on one side

### \*LEED® Information

Recycled Content  
Post Consumer 0%  
Post Industrial 0%

\*NOTE: LEED is a registered trademark of the U.S. Green Building Council.

## Storage

- Store in original unopened pails indoors at temperatures between 60 °F - 80 °F (16 °C - 27 °C) away from all sources of direct heat and ignition - this is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.
- Although there is no shelf life for GenFlex Cleaner, it's best to use within two years.

## Precautionary Data

- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not allowed.
- Avoid breathing vapors.
- Do not use as a primer for any Peel & Stick products.
- Refer to Safety Data Sheet for further information

Please contact Quality Building Services Technical Department at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*