


GenFast™ 2" Seam Plate

Item Description

2" Seam Plate

Item Number

W590010074



Product Information

Description

GenFast 2" (51 mm) Seam Plates are a galvanized metal disc that is used to secure GenFlex Reinforced Perimeter Strip (RPS) in GenFlex EPDM Systems. Please refer to current GenFlex specifications and details for specific applications.

Typical Properties	
Property	Typical Values
Metal	Steel with Galvalume® Coating
Diameter	2" (51 mm)
Thickness	0.030" (0.8 mm)
Hole Diameter	¼" (6 mm)
Edges	All Edges Deburred

Installation

Install GenFlex Seam Plates in accordance with current GenFlex specifications, details, and workmanship requirements.

Product Packaging	
Pail	1,000 pieces
Pail Weight	34 lb (15.4 kg)
Pallet	40 Pails

*LEED® Information

Post-Consumer Recycled Content: 8%
 Pre-Consumer Recycled Content: 17%
 Manufacturing Location: Cleveland, OH - Bryan, OH

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

Fasteners should be protected from moisture and kept dry at all times.
 If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

- Eye protection is recommended when installing fasteners and plates.
- Seam Plates are manufactured from galvanized metal. Precautions should be taken to avoid metal slivers, etc.
- Refer to Safety Data Sheet for additional information.
- Do not overdrive or underdrive fastener.
- Plates are designed to anchor GenFlex Reinforced Perimeter Strip (RPS) only.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.