

## GENFLEX CLEANER

### Item Description

Clear Solvent Cleaner

### Item Number

W590010092



## Product Information

### Description

GenFlex Cleaner is a clear solvent that can be used with a clean cotton rags to clean the seam area of EPDM membranes prior to the application of splice adhesive. The cleaner can also be used to remove contamination within TPO seams prior to heat welding of the laps.

Typical Properties	
Property	Typical Values
Composition	Naphthenic Solvents
Color	Clear
Solids	0%
Viscosity	Free Flowing
Weight	6.25 ± .25 lb/gal (.77 ± 0.05 kg/L)

### Installation

1. Apply liberal amounts of Cleaner to a clean rag.
2. Using a scrubbing motion, remove all contaminants at least 2" (50 mm) each way from the area to be seamed.
3. Remove all visible contaminants and maintain surfaces free from all moisture, oil, and other contaminants.
4. Change rags frequently to avoid depositing previously removed materials.
5. Allow the cleaned membrane to dry completely before seaming.

### Product Data

Property	Value
1 gallon (3.8 Liter)	4 per Carton
Flash Point	45 °F (-12 °C) TCC
Coverage Rate	200-250 ft <sup>2</sup> /gallon (4.9 – 6.1 m <sup>2</sup> /L) on one side.

### \*LEED® Information

#### Recycled Content

Post-Consumer	0%
Post Industrial	0%
V.O.C. Content	750 g/L

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

### Storage

12 Months; shelf life will be shortened if exposed to elevated temperatures.

### Precautionary Data

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke. Open all doors and windows. Close containers after use. Use with adequate ventilation. Avoid prolonged breathing of vapors. Avoid prolonged and repeated contact with skin. Store at temperature of 80 °F (27 °C) or below for maximum shelf life. Keep out of reach of children. Keep away from eyes. Use chemically resistant gloves. Review Safety Data Sheet (SDS) prior to use.

Please contact Technical Services at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*