

ALL PURPOSE LVOC CLEANER

Item Description

3 Gallon (11.4 Liter)

Item Number

W590030121

Product Information

Description

GenFlex All Purpose LVOC Cleaner is designed to clean and prepare GenFlex single-ply membranes to be welded, or to receive GenFlex Primers, Adhesives or Sealants, as noted in GenFlex specifications and details

Method of Application

1. Surfaces to be welded, or to receive primer, adhesive or sealant shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminants using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with GenFlex All Purpose LVOC Cleaner, moving in circular motions with heavy pressure over affected areas. Membrane with caked dirt, including in-service thermoplastic membranes, should be scrubbed using a GenFlex Scrub Pad and Handle wetted with All Purpose LVOC Cleaner, followed by wiping with clean rags to remove contaminants. On thermoplastic surfaces, the wipe with All Purpose LVOC Cleaner should be in one direction, flipping the rag often to avoid transferring contaminants.
3. Allow surfaces cleaned with GenFlex All Purpose LVOC Cleaner to dry completely (usually within 10 to 30 minutes) before welding or applying primer, adhesive or sealant per current GenFlex specifications and details.

Storage

- Store in original unopened container, at temperatures between 60 °F (16 °C) and 80 °F (27 °C), away from all sources of direct heat and ignition, until ready for use. This is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.
- Although there is no shelf life for Single-Ply LVOC Splice Wash, it is best to rotate stock and use within one year.

Coverage Rate

200-250 ft²/gallon (4.9 - 6.1 m²/L) on one side.

Precautions

- Review Safety Data Sheet (SDS) prior to use.
- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not permitted.
- Use of solvent-resistant neoprene gloves is required.
- Avoid contact with eyes and skin.
- Avoid breathing of vapors.
- Do not take internally.
- Cover container tightly when not in use.
- Use only in well ventilated areas.

LEED® Information

Recycled Content:

Post-Consumer 0%
 Post Industrial 0%

Manufacturing Location: South Bend, IN

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Typical Values
Solvents	Solvent Blend of Acetone and Mineral Spirits
Viscosity	Very Thin, Free Flowing
Weight / Gallon	6.593 ± 0.329 lb/gal (790 ± 39.42 g/l)
VOC Content	Less than 250 g/l

Packaging Data	
Pail	3 gal (11.4 L)
Weight	Appx 20 lb (9 kg)

Please contact Quality Building Services Technical Department at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.