


GENFLEX PEEL & STICK™ YELLOW SAFETY STRIP

Item Description

5½" x 100' (139.7 mm x 30.5 m)

Item Number

W590020200



Product Information

Description

GenFlex Peel & Stick Yellow Safety Strip consists of a white cured tape adhesive that is laminated to a yellow thermoplastic cover strip. GenFlex Peel & Stick™ Yellow Safety Strip is used for designating a safety perimeter around the roof edge, equipment and any other rooftop hazards, on all GenFlex membranes.

Typical Properties - Tape	
Property	Typical Values
Color	White
Base	Rubber Polymers
Solids	100%
Specific Gravity	0.98 ± 0.02 (H ₂ O=1)
Cure State	Cured
Width	5¾" – 0, + 1/16" (146 mm - 0 mm, + 1.65 mm)
Thickness	0.035" + 0.002", - 0.005" (0.89 mm + 0.05 mm, - 0.13 mm)
Length	100 Lineal Feet - 0, + 2' (30.5 m - 0, + 0.61 m)

Typical Properties - TPO	
Property	Typical Values
Base	TPO
Color	Yellow
Solids	100%
Specific Gravity	1.15 ± 0.05
Cure State	Cured
Width	5½" – 0, - 1/8" (140 mm - 0 mm, + 3.18 mm)
Thickness	0.030" + 10% (0.76 mm)
Length	100 Lineal Feet - 0, + 2' (30.5 m - 0, + 0.61 m)

Installation

GenFlex Clear Primer or Clear Primer LVOC must be applied with a scrub pad and handle when installing GenFlex Peel & Stick Yellow Safety Strip.

The application of the GenFlex Peel & Stick Yellow Safety Strip should be as follows:

1. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Thoroughly mix GenFlex Clear Primer. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required.
3. Clean all surfaces with a clean cotton rag, removing excess contamination prior to application of the primer.
4. With a scrub pad and handle, apply GenFlex Clear Primer to the GenFlex membrane and metal flange, using long and continuous back and forth strokes with heavy to moderate pressure along the bonding area until no streaks or puddling occurs.
5. Allow GenFlex Clear Primer to dry until slightly tacky to a dry finger touch.
6. Center the GenFlex Peel & Stick Yellow Safety Strip over the primed area, and remove the release paper from the tape. Apply the tape to the primed metal and/or GenFlex membrane.
7. Using a silicone coated rubber or steel hand roller, hand-roll the entire length of the tape into the primed surface, assuring adhesion.

*LEED® Information

Recycled Content

Post-Consumer 0%

Post Industrial 0%

Manufacturing Location Michigan Center, MI

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

Store in original unopened container indoors at temperatures between 60 °F and 80 °F (16 °C and 27 °C). Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C). When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

18 months; shelf life will be shortened if exposed to elevated temperatures.

Precautionary Data

Take care when moving, transporting, and handling, etc. to avoid sources of punctures and physical damage.

Contact GenFlex Roofing Systems Technical Department for specific recommendations.

Refer to Safety Data Sheet (SDS) for additional information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.