



NOTE:

1. REFER TO GENFLEX WEBSITE FOR THE MOST CURRENT INFORMATION.
2. MAXIMUM 6" (152 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS.
3. GENFLEX BATTEN STRIP MAY BE USED TO SECURE THE PEEL & STICK RPS TO THE WALL.. POLYMER BATTEN STRIP OR METAL ANCHOR BAR ACCEPTABLE FOR WOOD OR METAL SUBSTRATE. METAL ANCHOR BAR MUST BE USED WITH MASONRY SUBSTRATE.
4. STANDARD RPS MAY BE SUBSTITUTED FOR PEEL & STICK RPS.

BASE FLASHING AND TERMINATION NOT SHOWN FOR CLARITY. REFER TO APPROPRIATE TERMINATION & BASE TIE-IN DETAILS

THIS DETAIL IS FOR LAYOUT PURPOSE ONLY AND IS NON-SPECIFIC. REFER TO APPROPRIATE BASE TIE-IN DETAILS FOR SYSTEM SPECIFIC SECUREMENT OPTIONS

1" (25 mm) MAX. & 1/8" (3 mm) MIN.



PEEL & STICK RPS LAYOUT AT OUTSIDE CORNER

GENFLEX™

ACCEPTABLE SYSTEMS: **SEAM2SEAM™ EPDM**

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/06/2020

NOT TO SCALE

DETAIL NO.

S2S-BT-14