



USE APPROPRIATE TERMINATION

APPROPRIATE GENFLEX PRIMER

2" METAL PLATE POSITIONED 1/2" (13 mm) BEYOND WALL/CURB (SEE NOTE)

GENFAST FASTENER AND 2" METAL PLATE @ 12" (305 mm) O.C. MAX. (SEE NOTE)

SEAM2SEAM EPDM MEMBRANE MIN. 3" (76 mm) LAP PAST SEAM PLATE

APPROPRIATE GENFLEX PRIMER

CONTINUOUS BEAD OF SEAM2SEAM SEALANT

SEAM2SEAM EPDM MEMBRANE

GENFLEX INSULATION

SUBSTRATE

- NOTE:**
1. REFER TO GENFLEX WEBSITE FOR THE MOST CURRENT INFORMATION.
 2. MAXIMUM 6" (152 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS).
 3. REFER TO S2S-BT-16 & S2S-BT-17 FOR MEMBRANE SECUREMENT AT CORNERS.
 4. IN CASE OF OBSTRUCTION REFER TO DETAIL S2S-BT-10.



BASE TIE-IN WITH 2" METAL PLATES FASTENED TO DECK

GENFLEX™ ACCEPTABLE SYSTEMS: SEAM2SEAM™ EPDM

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

05/26/2020

DETAIL NO.

S2S-BT-6

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE