



- NOTE:
1. REFER TO GENFLEX WEBSITE FOR THE MOST CURRENT INFORMATION.
 2. REMOVE ALL EXISTING FLASHING, LEAD, ETC. PIPE SURFACE MUST BE FREE OF ALL RUST, GREASE, INSULATION, ETC.
 3. PENETRATION MUST BE ANCHORED TO ENSURE STABILITY.
 4. APPLY SEAM2SEAM SEALANT AROUND ENTIRE PERIMETER OF FLASHING. REFER TO S2S-LS-9 FOR PEEL & STICK EDGE TREATMENT.
 5. DO NOT USE WHEN SERVICE LINE TEMP. EXCEEDS 180 °F (82 °C). REFER TO S2S-P-4.
 6. ADDITIONAL MEMBRANE SECUREMENT REQUIRED WHEN PENETRATION EXCEEDS 12" (305 mm) DIAMETER. REFER TO BT DETAILS.



**PENETRATION WITH
FIELD FABRICATED FLASHING**

GENFLEX™

ACCEPTABLE SYSTEMS: **SEAM2SEAM™ EPDM**

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:
04/06/2020

DETAIL NO.
S2S-P-3

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE