



- NOTE:**
1. REFER TO GENFLEX WEBSITE FOR THE MOST CURRENT INFORMATION.
 2. INSTALL METAL WORK TO MANUFACTURER'S REQUIREMENTS OR SMACNA RECOMMENDATIONS.
 3. SEAM2SEAM SEALANT IS REQUIRED ALONG ENTIRE UPSLOPE EDGE OF PEEL & STICK FLASHING WHEN ROOF SLOPE IS 1" (25 mm) PER FOOT OR GREATER.
 4. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES OR 200 lb PER LINEAR FOOT MINIMUM IN ANY GIVEN DIRECTION.
 5. FLANGE OF METAL MUST BE FULLY SUPPORTED BY WOOD AND TERMINATED AT LEAST 1/2" (13 mm) FROM EDGE OF WOOD.
 6. IF THE FLANGE OF THE METAL EDGE IS NOT COMPLETELY COVERED WITH PEEL & STICK FLASHING, THEN AN ADDITIONAL PIECE OF PEEL & STICK FLASHING SHALL BE INSTALLED AT ALL METAL SPLICES. REFER TO S2S-RE-28.



**ROOF EDGE WITH FASCIA METAL
BY OTHERS**

GENFLEX™ ACCEPTABLE SYSTEMS: SEAM2SEAM™ EPDM

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

06/01/2020

DETAIL NO.

S2S-RE-23

NOT TO SCALE