



NOTE:

1. REFER TO GENFLEX WEBSITE FOR MOST CURRENT INFORMATION.
2. WATERTIGHT INTEGRITY OF THE WALL AND COPING MUST BE MAINTAINED BY OTHERS.
3. COPING STONE ATTACHMENT IS THE RESPONSIBILITY OF THE SPECIFIED CONTRACTOR.
4. ANCHOR BOLT SECUREMENT LUG MUST BE INSTALLED IN ACCORDANCE WITH MASONRY STANDARDS AND LOCAL BUILDING CODES.
5. EXTEND SEAM2SEAM EPDM MEMBRANE TO OUTSIDE FACE OF WALL.
6. CONTINUOUS BEAD OF SEAM2SEAM WATERSTOP ALONG ENTIRE EDGE OF EPDM AND WALL. WATERSTOP ALSO APPLIED AROUND ANCHOR.

USE APPROPRIATE BASE TIE-IN



**TERMINATION AT TOP OF WALL
WITH COPING STONE**

GENFLEX™

ACCEPTABLE SYSTEMS: **SEAM2SEAM™ EPDM**

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

04/06/2020

DETAIL NO.

S2S-T-11

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE