



- NOTE:**
1. REFER TO GENFLEX WEBSITE FOR MOST CURRENT INFORMATION.
  2. GENFAST FASTENER WITH TERMINATION CAULK OVER FASTENER HEADS. TERMINATION CAULK ALSO REQUIRED ALONG ENTIRE EDGE OF CURB FLANGE.
  3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES OR 200 lb PER LINEAR FOOT IN ANY DIRECTION.
  4. USE ACCEPTABLE GENFLEX PRIMER TO CLEAN AND PRIME EPDM MATING SURFACES PRIOR TO REMOVAL OF SEAM2SEAM SEAM RELEASE LINER.
  5. SEAM2SEAM SEALANT IS REQUIRED OVER ALL FIELD AND FLASHING SEAMS.



**TERMINATION AT R.T.U.  
UNIT FLANGE ABOVE MEMBRANE**

GENFLEX™ ACCEPTABLE SYSTEMS: SEAM2SEAM™ EPDM

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

06/01/2020

DETAIL NO.

**S2S-T-14**

NOT TO SCALE