



**NOTE:**

1. REFER TO GENFLEX WEBSITE FOR MOST CURRENT INFORMATION.
2. REGULAR MAINTENANCE OF COUNTER-FLASHING AND SEALANT REQUIRED. NOT INCLUDED AS PART OF THE GENFLEX WARRANTY.
3. METAL COUNTER-FLASHING SHALL BE 24 GAUGE PRE-FINISHED STEEL OR .032" (8 mm) MIN. ALUMINUM FORMED WITH HEMMED LOWER EDGE.
4. INSTALL METAL WORK IN ACCORDANCE WITH CURRENT SMACNA RECOMMENDATIONS.

**MASONRY AND CONCRETE  
WALLS / CURBS MUST BE  
WATERPROOFED AND  
MAINTAINED IN ORDER  
FOR ANY SURFACE  
MOUNTED TERMINATION  
TO BE EFFECTIVE.**



**TERMINATION WITH REGLET COUNTERFLASHING**

**GENFLEX™**

ACCEPTABLE SYSTEMS: **SEAM2SEAM™ EPDM**

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

04/06/2020

NOT TO SCALE

DETAIL NO.

**S2S-T-3**