

GENFAST™ #14 PREASSEMBLED SCREW AND PLATE

Item Description

9" 10" 11" 12" 14"

Item Number W590055123

W590055124 W590055125 W590055126 W590055127



Product Information

Description

GenFast #14 Preassembled Screws and Plates may be used in any GenFlex system for attachment of roofing insulations into steel, wood, and lightweight concrete (into steel deck) substrates.

Typical Properties		
Screw Property	Typical Values	
Metal	SAE 1022 Heat Treated	
Color	Black	
Diameter and Thread	#14 Modified Buttress	
Head Style	#3 Phillips	
Corrosion Coating	SPEX™	
Fastener Tip	Patented X-Point	
Plate Property	Typical Values	
Material	Polypropylene	
Diameter	3" (76 mm) round	
Corrosion Coating	Non-corrosive plastic	

Installation

GenFast #14 Preassembled Screw length is determined as follows:

Steel Deck – Minimum of 1" (25 mm) required penetration Wood Deck – Minimum of 1" (25 mm) required penetration Check current GenFlex specifications for exceptions and/or changes.



Product Data

Screw Length	Thread Length	Pieces/Carton
9" (228.6 mm)	4" (101.6 mm)	250
10" (254 mm)	4" (101.6 mm)	200
11" (279.4 mm)	4" (101.6 mm)	200
12" (304.8 mm)	4" (101.6 mm)	200
14" (355.6 mm)	4" (101.6 mm)	150

*LEED® Information

Recycled Content:		
Post-Consumer:	25%	
Pre-Consumer	0%	
*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.		

Storage

Fasteners should be protected from moisture and kept dry at all times. If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

Eye protection is recommended when installing fasteners and plates. Refer to Safety Data Sheet (SDS) for further information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.