

NOTE:

- REFER TO THE GENFLEX[™] WEBSITE FOR THE MOST CURRENT INFORMATION.
- 2. REFER TO DETAIL EZT-PS-LS-01 OR EZT-PS-LS-02 FOR WELD WIDTH.
- 3. COMPRESSIBLE TUBE (SUPPLIED BY OTHERS)
 DIAMETER MUST EXCEED THE DECK OPENING
 BY 50% MIN. OR DESIGNATED MOVEMENT
 (WHICH EVER IS GREATER)
- MAXIMUM 10" (254 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS.
- 5. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-PS-LS-04 FOR CUT EDGE SEALANT APPLICATION.
- 6. REFER TO EZT-PS-LS-01 FOR ADDITIONAL LAP SPLICE REQUIREMENTS.
- APPROVED PRIMER REQUIRED ON ALL VERTICAL SURFACES.
- 8. REFER TO GENFLEX TIS SHEETS AND APPLICATION GUIDES FOR LIST OF COMPATIBLE SUBSTRATES WITH EZ TPO PEEL & STICK MEMBRANE.

THIS DETAIL IS NOT
ACCEPTABLE FOR PAVER
BALLAST SYSTEMS.
CONTACT GENFLEX FOR
ADDITIONAL INFORMATION.

MAXIMUM WARRANTY: 20 Years



EXPANSION JOINT (FIELD FABRICATED) WITH WELDED SPLICE - ROOF TO WALL

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™ SELF ADHERED

UE / DEL/(0)(0)

ISSUE / REVISION DATE:

DETAIL NO.

05/01/2023

EZT-PS-E-01

(800) 443-4272 www.genflex.com

NOT TO SCALE