



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR THE MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-PS-LS-01 FOR WELD WIDTH.
3. REMOVE ALL EXISTING FLASHING, LEAD, ETC. PIPE SURFACE MUST BE FREE OF ALL RUST, GREASE, INSULATION, ETC.
4. PIPE MUST BE ANCHORED TO ENSURE STABILITY.
5. NO WRINKLES OR FOLDS UNDER CLAMPING RING.
6. DO NOT USE WHEN SERVICE LINE TEMP. EXCEEDS 160 °F (71 °C). REFER TO UT- P-06 & UT-P-07.
7. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-PS-LS-04 FOR CUT EDGE SEALANT APPLICATION.
8. REFER TO GENFLEX TIS SHEETS AND APPLICATION GUIDES FOR LIST OF COMPATIBLE SUBSTRATES WITH GENFLEX EZ TPO PEEL & STICK MEMBRANE



**PENETRATION WITH GENFLEX
NON-REINFORCED FLASHING**

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™ SELF ADHERED

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

05/01/2023

DETAIL NO.

EZT-PS-P-03

(800) 443-4272 www.genflex.com

NOT TO SCALE