



**NOTE:**

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-PS-LS-01 FOR WELD WIDTH.
3. MAXIMUM 10" (254 mm) LONG FASTENERS MAX 6" (152 mm) FROM TRANSITION (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENT).
4. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-PS-LS-04 FOR CUT EDGE SEALANT APPLICATION.
5. REFER TO GENFLEX TIS SHEETS AND APPLICATION GUIDES FOR LIST OF COMPATIBLE SUBSTRATES WITH EZ TPO PEEL & STICK MEMBRANE
6. EZ TPO PEEL & STICK MEMBRANE DOES NOT REQUIRE INTERMEDIATE ATTACHMENT UP TO 5' (1.52 m).
7. IF INTERMEDIATE ATTACHMENT IS REQUIRED, COMPLETE AS FOLLOWS:
  - UP TO 5' (1.52 m) WALL HEIGHT- NONE REQUIRED
  - 5' (1.52 m) - 10' (3.05 m) WALL HEIGHT - ONE ATTACHMENT AT 1/2 THE WALL HEIGHT
  - ABOVE 10' (3.05 m) - ONE ATTACHMENT EVERY 3' (0.91 m)
8. APPROPRIATE PRIMER REQUIRED WHEN EZ TPO PEEL & STICK MEMBRANE IS APPLIED TO VERTICAL SURFACES.



**GENFLEX EZ TPO PEEL & STICK  
WALL FLASHING DETAIL**

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™

ACCEPTABLE SYSTEMS: EZ TPO PEEL & STICK™ SELF ADHERED

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

05/01/2023

DETAIL NO.

**EZT-PS-WF-01**

(800) 443-4272 www.genflex.com

NOT TO SCALE