



- NOTE:
1. REFER TO GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
  2. COMPRESSIBLE TUBE (SUPPLIED BY OTHERS) DIAMETER MUST EXCEED THE DECK OPENING BY 50% MIN. OR DESIGNED MOVEMENT (WHICH EVER IS GREATER). LEAVE RELEASE LINER ON P&S MEMBRANE AT COMPRESSIBLE TUBE AREA.
  3. BAR ANCHOR MAY BE USED IN LIEU OF 2" METAL PLATES FOR MAS AND FULLY ADHERED SYSTEMS ONLY. REFER TO "BT" DETAILS FOR SPECIFIC BASE TIE-IN INFORMATION, REQUIREMENTS AND OPTIONS.
  4. MAXIMUM 10" (254 mm) LONG FASTENERS, (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS).
  5. REFER TO EZE-PS-LS-06 FOR ADDITIONAL LAP SPLICE REQUIREMENTS.



**EXPANSION JOINT (FIELD FABRICATED) WITH  
PEEL & STICK RPS & WOOD NAILER ROOF TO ROOF**

ACCEPTABLE SYSTEMS: EZ EPDM PEEL & STICK™ SELF ADHERED

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION  
DATE:

07/28/2023

DETAIL NO.

EZE-PS-E-02

(800) 443-4272 www.genflex.com

NOT TO SCALE