SAFETY DATA SHEET



1. Identification

GENFLEX EZ TPO Clear Cut Edge Sealant Product identifier

Other means of identification

W59TPOC001 **Product code**

Recommended use Roofing and Architectural Sealant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Holcim Solutions and Products US, LLC Distributed by

Address 26 Century Boulevard, Suite 205

Nashville, TN 37214

GenFlex™ is a Holcim Solutions and Products US, LLC brand

Website Genflex.com

Telephone Number Technical: 1-800-443-4272

Emergency Telephone

Number

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Hazardous to the aquatic environment, acute

Hazardous to the aquatic environment,

long-term hazard

Not classified.

Category 3

Category 3

OSHA defined hazards

Label elements





Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes eye irritation. May cause drowsiness

or dizziness. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face

protection.

1/9 946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None

3. Composition/information on ingredients

Mixtures

Chemical name Distillates, petroleum, hydrotreated light		CAS number	%
		64742-47-8	*
Stoddard solvent		8052-41-3	*
Constituents			
Chemical name	Common name and synonyms	CAS number	%
n-Nonane		111-84-2	1 - 5

Trimethylbenzene Composition comments

* The petroleum solvent used in this product is either CAS 64742-47-8 or CAS 8052-41-3 and present at a concentration of 68 - 72%.

25551-13-7

1 - 5

All concentrations are in percent by weight unless otherwise indicated.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and

delayed

Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

GENFLEX EZ TPO Clear Cut Edge Sealant
946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. Carbon oxides (COx). During fire, gases hazardous to health may be formed such as:

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Avoid breathing mist/vapors.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value	
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	
JS. ACGIH Threshold Limit	Values		
Components	Туре	Value	
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Constituents	Туре	Value	
Trimethylbenzene (CAS 25551-13-7)	TWA	10 ppm	
n-Nonane (CAS 111-84-2)	TWA	200 ppm	
JS. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Distillates, petroleum, nydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Constituents	Туре	Value	
Trimethylbenzene (CAS 25551-13-7)	TWA	125 mg/m3	
		25 ppm	
n-Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
gical limit values	No biological exposure limits noted f	or the ingredient(s).	
opriate engineering	Explosion proof general and local ov	haust ventilation. Good general ventilation should be	י וופפל

Bio

App controls

Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Chemical respirator with organic vapor Eye/face protection

cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Nitrile gloves are recommended.

Skin protection

Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

> limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Appropriate respirator selection should be made by a qualified

professional.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

GENFLEX EZ TPO Clear Cut Edge Sealant

946389 Version #: 02 Revision date: 23-January-2023 4/9 Issue date: 23-January-2023

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Clear. Colorless.

Odor Hydrocarbon.

Odor threshold Not available.

pH Not determined.

Melting point/freezing point Not determined.

Initial boiling point and boiling

> 316.4 - < 381.2 °F (> 158 - < 194 °C)

range

Flash point 107.6 °F (42 °C) Closed Cup

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Explosive limit - upper (%)

Vapor pressure

Not determined.

Relative density Solubility(ies)

Vapor density

Solubility (water) Not determined.

Partition coefficient Not applicable, product is a mixture.

(n-octanol/water)

Auto-ignition temperature Not self-igniting.

Decomposition temperature Not applicable as the product is not unstable.

Not determined.

Not determined.

Viscosity > 4000 - < 6000 cP (75.2 °F (24 °C))

Other information Solids: 28 - 32%

Density 6.88 lb/gal

6.88 lb/gal 0.82 g/ml

Explosive properties Not explosive.

Kinematic viscosity Not determined.

Oxidizing properties Not oxidizing.

VOC 580 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

GENFLEX EZ TPO Clear Cut Edge Sealant
946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023

Skin contact Causes skin irritation. Eye contact Causes eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May

cause redness and pain.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Stoddard solvent (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of this product.

No data available for this product. **Bioaccumulative potential**

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

> material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023

14. Transport information

DOT

UN1133 **UN** number Adhesives **UN proper shipping name**

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Ш **Packing group Environmental hazards**

> No. Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T2, TP1

Packaging exceptions 150 Packaging non bulk 173 Packaging bulk 242

IATA

UN1133 **UN** number Adhesives **UN proper shipping name**

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN1133 **UN** number UN proper shipping name **ADHESIVES**

Transport hazard class(es) Class 3 Subsidiary risk Packing group Ш

Environmental hazards

Marine pollutant No. **EmS** F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not established.

n-Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Distillates, petroleum, hydrotreated light Listed. (CAS 64742-47-8)

n-Nonane (CAS 111-84-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

GENFLEX EZ TPO Clear Cut Edge Sealant 946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023

SDS US

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation categories

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. 25551-13-7 1 - 5 Trimethylbenzene

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Distillates, petroleum, hydrotreated light (CAS 64742-47-8)

n-Nonane (CAS 111-84-2)

Stoddard solvent (CAS 8052-41-3)

Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

Distillates, petroleum, hydrotreated light (CAS 64742-47-8)

n-Nonane (CAS 111-84-2)

Stoddard solvent (CAS 8052-41-3)

Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates, petroleum, hydrotreated light (CAS 64742-47-8)

n-Nonane (CAS 111-84-2)

Stoddard solvent (CAS 8052-41-3)

Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

Distillates, petroleum, hydrotreated light (CAS 64742-47-8)

n-Nonane (CAS 111-84-2)

Stoddard solvent (CAS 8052-41-3)

Trimethylbenzene (CAS 25551-13-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, Cumene, Ethylbenzene, which are known to the State of California to cause cancer, and Benzene, Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Cumene (CAS 98-82-8) Listed: April 6, 2010 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Benzene (CAS 71-43-2)

Cumene (CAS 98-82-8)

Distillates, petroleum, hydrotreated light (CAS 64742-47-8)

Ethylbenzene (CAS 100-41-4)

Stoddard solvent (CAS 8052-41-3)

Toluene (CAS 108-88-3)

GENFLEX EZ TPO Clear Cut Edge Sealant

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 23-January-2023 **Revision date** 23-January-2023

Version # 02

United States & Puerto Rico

HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 0

Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this **Disclaimer**

Toxic Substances Control Act (TSCA) Inventory

information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper

use. The information in the sheet was written based on the best knowledge and experience

currently available.

GENFLEX EZ TPO Clear Cut Edge Sealant

SDS US

946389 Version #: 02 Revision date: 23-January-2023 Issue date: 23-January-2023 Yes