



- NOTE:
- 1. REFER TO WWW.GENFLEX.COM FOR MOST CURRENT INFORMATION.
 - 2. THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE OUTSIDE WALL.
 - 3. GRANULES MUST BE EMBEDDED WHEN THERMALLY FUSING GRANULE SURFACED CAP SHEET.
 - 4. FLASHING LAPS MUST BE OFFSET FROM FIELD LAPS BY A MINIMUM OF 12" (305 mm).
 - 9. IF THE PARAPET EXCEEDS 18" (457 mm) IN HEIGHT, HOT ASPHALT MUST NOT BE USED TO ATTACH FLASHING.
 - 10. PARAPETS WITH NAILABLE SUBSTRATES MUST HAVE A GENFLEX BASE SHEET MECHANICALLY ATTACHED IN ACCORDANCE WITH THE FOLLOWING SPACING:
UP TO 24" (305-610 mm) 9" (152 mm) ON CENTERS
24-36" (610-914 mm) 6" (228 mm) ON CENTERS
FIELD OF WALL ONE PER FT² (929 cm²)

**THIS DETAIL APPLIES
TO SBS MEMBRANES ONLY**

	BASE TIE-IN - HOT ADHESIVE APPLIED		MAXIMUM WARRANTY: 20 Years	
			ISSUE / REVISION DATE: 05/07/2025	DETAIL NO. MB-BT-13
	GENFLEX™	ACCEPTABLE SYSTEMS: MODIFIED BITUMEN	NOT TO SCALE	
GENFLEX: (800) 443-4272 www.genflex.com				