



NOTE:

1. REFER TO WWW.GENFLEX.COM FOR MOST CURRENT INFORMATION.
2. THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE OUTSIDE WALL.
3. GRANULES MUST BE EMBEDDED WHEN THERMALLY FUSING GRANULE SURFACED CAP SHEET.
4. FLASHING LAPS MUST BE OFFSET FROM FIELD LAPS BY A MINIMUM OF 12" (305 mm).
5. PARAPETS WITH NAILABLE SUBSTRATES MUST HAVE A GENFLEX BASE SHEET MECHANICALLY ATTACHED IN ACCORDANCE WITH THE FOLLOWING SPACING:
 UP TO 24" (305-610 mm) 9" (152 mm) ON CENTERS
 24-36" (610-914 mm) 6" (228 mm) ON CENTERS
 FIELD OF WALL ONE PER FT² (929 cm²)

**THIS DETAIL APPLIES
TO APP AND SBS MEMBRANES**



BASE TIE IN - TORCH APPLIED

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

05/07/2025

DETAIL NO.

MB-BT-14

GENFLEX™

ACCEPTABLE SYSTEMS: MODIFIED BITUMEN

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE