



- NOTE:
- 1. REFER TO WWW.GENFLEX.COM FOR MOST CURRENT INFORMATION.
 - 2. THIS DETAIL ALLOWS FOR BUILDING MOVEMENT IN BOTH DIRECTIONS.
 - 3. FLASHING REQUIREMENTS TYPICAL FOR BOTH SIDES OF THE EXPANSION JOINT.
 - 4. WOOD NAILERS MUST BE INSTALLED WITH SUITABLE FASTENERS TO MEET APPLICABLE BUILDING CODES.
 - 5. ALL SHEET METAL IS TO BE INSTALLED PER SMACNA GUIDELINES.
 - 6. GRANULES MUST BE EMBEDDED WHEN THERMALLY FUSING GRANULE SURFACED CAP SHEET.
 - 7. FLASHING LAPS MUST BE OFFSET FROM FIELD LAPS BY A MINIMUM OF 12" (305 mm).



EXPANSION JOINT WITH METAL COVER

GENFLEX™

ACCEPTABLE SYSTEMS: MODIFIED BITUMEN

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

05/07/2025

NOT TO SCALE

DETAIL NO.

MB-E-1