

SHEET METAL HOOD (BY OTHERS) WITH
CONTINUOUS BEAD OF TERMINATION CAULK

CONTINUOUS BEAD OF TERMINATION CAULK

STAINLESS STEEL CLAMPING RING

PRE-MOLDED QUICKSEAM PIPE FLASHING

APP MODIFIED BITUMEN GRANULE
SURFACED CAP SHEET

BASE AND INTERPLY SHEETS
REQUIRED FOR 15 & 20 YEAR SYSTEMS

COVERBOARD (AS REQUIRED)

INSULATION

INSULATION

SUBSTRATE

ROUND PENETRATION

NOTE:

1. REFER TO WWW.GENFLEX.COM FOR MOST CURRENT INFORMATION.
2. REFER TO DETAILS MB-LS-1, MB-LS-2, & MB-LS-3 FOR APPROPRIATE LAP SEALING APPLICATIONS.
3. PRE-MOLDED QUICKSEAM PIPE FLASHING MAY BE CUT TO HEIGHT, BUT NO LOWER THAN REINFORCING RING (NO WRINKLES OR FOLDS UNDER CLAMPING RING).
4. GRANULES MUST BE EMBEDDED WHEN THERMALLY FUSING GRANULE SURFACED CAP SHEET.
5. TO USE THIS DETAIL ON A SBS ROOF, INSTALL THE TARGET IN MB COLD ADHESIVE.

INSTALL TARGET MEMBRANE SO THAT IT
EXTENDS A MINIMUM OF 1/2" (13 mm) UP PIPE

APP 160 TARGET PATCH HEAT FUSED IN
PLACE (SEE NOTE #5) A MIN OF 4" (102 mm)
LARGER THAN DIAMETER OF QUICKSEAM
PIPE FLASHING (TORCH TOP OF TARGET SO
THAT SURFACE IS GLOSSY BEFORE
APPLYING QUICKSEAM PIPE FLASHING)

COVERBOARD (AS REQUIRED)

INSULATION

INSULATION

SUBSTRATE



**PEEL & STICK PIPE FLASHING
WITH APP 160 TARGET**

GENFLEX™

ACCEPTABLE SYSTEMS: MODIFIED BITUMEN

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION
DATE:

05/21/2025

NOT TO SCALE

DETAIL NO.

MB-P-5