

ASPHALT

Roofing Systems



REAL-WORLD TOUGH, CONTRACTOR TRUSTED.

GenFlex asphalt is designed to work the way you do – fast, tough, and built to last. GenFlex asphalt roofing systems are engineered for real-world performance. With both SBS and APP modified bitumen options available, these systems offer the flexibility to meet your installation needs. Designed with built-in redundancy, they provide multiple layers of protection to withstand harsh climates, demanding timelines, and the unexpected. GenFlex delivers proven protection, rugged durability, and the confidence to get the job done right – and keep it that way.



SBS

GenFlex SBS modified bitumen systems use a rubber-based polymer technology that delivers strength and flexibility, even in extreme cold. With multiple install options and outstanding durability, it's the go-to solution when the job demands both performance and versatility. GenFlex SBS is one of the most versatile low-slope solutions in our lineup. It's compatible with a wide range of application methods – including cold-applied, torch, mechanically fastened, and hot asphalt – giving your crew the freedom to install it your way, without compromise.

APP

GenFlex APP systems are designed for speed and long-term UV resistance, with a thermoplastic bitumen blend that can handle the heat. Ideal for torch-applied efficiency and open commercial decks, it's the reliable choice for hardworking crews in demanding conditions. GenFlex APP delivers the strength and weather resistance you expect from asphalt, with the efficiency and clean handling you need on the job. Formulated with premium asphalt, our APP membranes install smooth, stay straight, and resist hooking – so your lines stay clean and your crew stays productive. GenFlex APP gives you a roof that performs tough and looks sharp for the long haul.

YOUR GO-TO MODIFIED BITUMEN SYSTEMS

From challenging climates to fast-turn installations, GenFlex SBS and APP roofing systems deliver proven performance with the flexibility to fit your job.

	GenFlex SBS	GenFlex APP
Material Advantage	Rubber-modified asphalt for flexibility and movement	Plastic-modified asphalt for UV resistance and durability
Best For	Cold climates, complex roofs	Warm climates, open decks
Flexibility	High – ideal for freeze/thaw cycles and shifting structures	Moderate – more rigid and stable for long-term wear
UV & Heat Resistance	Moderate – best with granules or coating	High – designed for direct exposure
Installation Options	Cold-applied, torch-applied, or hot asphalt	Torch-applied or cold-applied
Surface Types	Smooth or granule-surfaced sheets	Smooth or granule-surfaced sheets
Go-To Applications	Schools, hospitals, retrofits, and detailed roofs	Warehouses, retail centers, large-scale new construction

WHY GENFLEX?




▼ INSTALLER FOCUSED

Multiple methods to match your crew and project



▼ JOBSITE READY

Products that install fast and perform in tough conditions



▼ PROVEN MATERIALS

Durable systems backed by a brand that understands the field



▼ SIMPLIFIED SUPPORT


Tools, technical help, and real people when you need them

WARRANTY OPTIONS

GenFlex offers a range of warranty coverages to suit various project needs:

- ▼ **Material Only Warranty**
5, 10, 15, or 20 years
- ▼ **Roofing System Warranty**
5, 10, 15, or 20 years
Available to GenFlex Licensed Contractors

For detailed warranty requirements, including wind speed coverage and system specifications, refer to the GenFlex Asphalt Design and Application Guide on our website.



LOOKING FOR TECHNICAL RESOURCES?

Visit [genflex.com/technical-info](https://www.genflex.com/technical-info) for additional information including:

- ▼ **Product Data Sheets**
- ▼ **Safety Data Sheets**
- ▼ **Installation Guides**
- ▼ **Product Details**
- ▼ **Brochures**



ASPHALT THAT WORKS LIKE YOU DO.

Whether you're roofing in the cold or torching in the heat, GenFlex gives you the confidence to get in, get it done, and confidently move to the next job – with performance that lasts.

For more information or to place an order, please contact your GenFlex representative or visit www.genflex.com.



SBS MODIFIED BITUMEN MEMBRANES

ASTM CLASSIFICATION			MEMBRANE	TOP SURFACING	MATERIAL #	MEMBRANE TYPE / USE				REINFORCEMENT TYPE		APPLICATION				ROLL SPECIFICATIONS			
ASTM	Type	Grade		Granule Color		Cap	Ply/ Interply	Base		Fiberglass	Polyester	Hot Applied	Cold Applied	Torch Applied	Mech. Fastened	Roll Dimensions	Net Coverage	Membrane Thickness	Roll Weight
6163	I	S	SBS Base Sheet	Smooth / Sand	W81FSS0825		X	X		X		X	X		X	39.4" x 50'	149 sqft (13.8 m²)	90 mil (2.3 mm)	95 lb (43.1 kg)
6163	I	S	SBS Glass Torch Base	Smooth / Sand	W81FSP1225		X	X		X				X	X	39.4" x 33'6"	98 sqft (9.1 m²)	120 mil (3.0 mm)	90 lb (40.8 kg)
6163	I	S	SBS Glass Torch Base 1.5 Square	Smooth / Sand	W81FSP0925		X	X		X				X	X	39.4" x 50'	149 sqft (13.8 m²)	90 mil (2.28 mm)	98 lb (44.45 kg)
6164	I	S	SBS Poly Torch Base	Smooth / Sand	W81PSP1625		X	X			X			X	X	39.4" x 33'6"	98 sqft (9.1 m²)	120 mil (3.0 mm)	89 lb (40.37 kg)
6164	I	S	SBS Smooth	Smooth / Sand	W81PSS1400		X	X			X	X	X		X	39.4" x 33'6"	98 sqft (9.1 m²)	145 mil (3.7 mm)	107.5 lb (48.8 kg)
6164	I	G	SBS Cap	White	W81PWS1600N	X					X	X	X			39.4" x 33'6"	98 sqft (9.1 m²)	155 mil (3.9 mm)	113.5 lb (51.48 kg)
6164	I	G	SBS FR	White	W81PWS160FN	X					X	X	X			39.4" x 33'6"	98 sqft (9.1 m²)	155 mil (3.9 mm)	114.5 lb (51.94 kg)
6164	I	G	SBS FR Torch	White	W81PWP16FT2N	X					X			X		39.4" x 33'6"	98 sqft (9.1 m²)	160 mil (4.1 mm)	116.5 lb (52.84 kg)
6164	II	G	SBS Premium FR	White	W81HWS160FN	X					X	X	X			39.4 " x 33'6"	98 sqft (9.1 m²)	160 mil (4.1 mm)	115.5 lb (52.39 kg)
6164	II	G	SBS Premium FR Torch	White	W81HWS16FTN	X					X			X		39.4 " x 33'6"	98 sqft (9.1 m²)	160 mil (4.1 mm)	116.5 lb (52.84 kg)

APP MODIFIED BITUMEN MEMBRANES

ASTM CLASSIFICATION			MEMBRANE	TOP SURFACING	MATERIAL #	MEMBRANE TYPE / USE				REINFORCEMENT TYPE		APPLICATION				ROLL SPECIFICATIONS			
ASTM	Type	Grade		Granule Color		Cap	Ply/ Interply	Base		Fiberglass	Polyester	Hot Applied	Cold Applied	Torch Applied	Mech. Fastened	Roll Dimensions	Net Coverage	Membrane Thickness	Roll Weight
D6222	I	S	APP 160	Smooth / Sand	W80APP0162	X	X	X			X			X	X	39.4" x 32'10"	98 sqft (9.1 m2)	154 mil (3.9 mm)	110.5 lb (50.12 kg)
D6222	I	S	APP 160 Cool	Smooth / Sand	W80PTT1600	X	X	X			X		X		X	39.4" x 32'10"	98 sqft (9.1 m2)	154 mil (3.9 mm)	110.5 lb (50.12 kg)
D6222	I	G	APP 180	White	W80PWP1800N	X					X			X		39.4" x 32'10"	98 sqft (9.1 m2)	165 mil (4.2 mm)	115.5 lb (52.39 kg)
D6222	I	G	APP 180	Black	W80PBP1800N	X					X			X		39.4" x 32'10"	98 sqft (9.1 m2)	165 mil (4.2 mm)	115.5 lb (52.39 kg)
D6222	I	G	APP 180 Cool	White	W80PWS180CN	X					X		X			39.4" x 32'10"	98 sqft (9.1 m2)	165 mil (4.2 mm)	116.5 lb (52.84 kg)
D6222	I	G	APP 180 Cool	Black	W80PBS180CN	X					X		X			39.4" x 32'10"	98 sqft (9.1 m2)	165 mil (4.2 mm)	116.5 lb (52.84 kg)



www.GenFlex.com

© 2025 Amrize. All Rights Reserved.
GenFlex is part of the Amrize family of brands.

WE DON'T JUST DELIVER MATERIALS, WE DELIVER SOLUTIONS THAT HELP OUR PARTNERS SUCCEED

At GenFlex, we believe success starts with partnership. By understanding your unique roofing challenges, we provide tailored solutions that ensure durability, ease of installation, and lasting performance. Our commitment to quality, innovation, and customer support means we're with you every step of the way—from selecting the right materials to providing comprehensive warranty coverage for peace of mind. Together, we turn challenges into opportunities, equipping you with the tools and expertise needed to deliver exceptional results on every project. At GenFlex, your success is our mission, and we're here to help you achieve it. **Questions?**

Email us at GenFlexSolutions@amrize.com

Code Compliance

Compliance is more than a requirement—it's our commitment to quality, safety, and innovation, helping make sure your project is built to last while meeting legal and environmental standards. With GenFlex, you can trust that your roofing system is designed to perform and comply at the highest level. GenFlex has systems that have achieved Underwriters Laboratories™ (UL) classifications and Factory Mutual (FM) approvals. GenFlex systems are also listed by International Code Council™ (ICC) and Miami Dade County. Refer to the appropriate agency publication for other listings, or contact the GenFlex Roofing Systems technical department at **1-800-443-4272**, 7:30 AM - 4:30 PM Central Time.