

## Ceramic Coated Roofing Granules

### Item Description

White

Black

### Item Number

W80RACGGWHN

W80RACGGBKN



## Product Information

### Description

Ceramic coated roofing granules are made available in 50 lb (22.7 kg) metal pails.

### Installation

GenFlex recommends that granules be applied to areas of asphalt “bleed-out” while the asphalt is still in a molten state. Areas of “bleed-out” at inside and outside corners require application of granules.

### Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Minimize the amount of dust generated when applying or handling this product. Use in well ventilated area.

### \*LEED® Information

Recycled Content

Post-Consumer 0%

Post Industrial 0%

Manufacturing Location Beech Grove, IN

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Product Packaging	
Property	Value
Pail	5-gallon (18.9L)
Weight	50 lb (22.7 kg)
Pallet Size	48" x 39" (1.2 m x 1.0 m)
Pails per Pallet	36
Pallet Weight	2000 lb (907 kg)
Pallets per Truckload	24

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*