


Product Data Sheet



GenFast™ Metal Bar Anchor

Item Description	Item Number
10' (3 m)	W590010073
Cardboard tube of 50 Bar Anchors	

Description

GenFast Metal Bar Anchors are used for the mechanical attachment of the EPDM and TPO membranes in mechanically attached roofing systems. They can also be used to attach membrane at the perimeter of the building and around penetrations per current GenFlex Technical Specifications.

Method of Application

Attach bar anchors to the roof substrate or penetration using the appropriate GenFast fastener. Do not overdrive or underdrive fasteners. Start at one end of the anchor bar and fasten towards the other to reduce bowing between fasteners.

Storage

Store in original unopened tubes protected from weather.

LEED® Information

Post-Consumer Recycled Content: 8%

Post Industrial Recycled Content: 17%

Manufacturing Location: Cleveland, OH

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Test Method
Material	Galvalume® AZ 55
Corrosion Resistance	Meets FM No. 4470 criteria
Length x width x thickness	10' (3 m) x 1" (25.4 mm) x 0.04"/0.05" (1.13 mm/1.29 mm)
Holes	0.343" (8.71 mm) diameter, at 6" (152 mm) o.c.

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.

PDS 1202

September 9, 2025

Sales: (800) 428-4442

Technical: (800) 443-4272

Page 1