

Product Data Sheet



Termination Caulk

Item Description	Item Number
300 ml (10 oz) Cartridge	W590010172
*2 Cartridges / Carton	

Description

GenFlex Termination Caulk is a one-part polyurethane moisture-curing sealant. It can be used as an exterior sealant on termination bars or used to caulk sheet metal, masonry, concrete block or as a fastener sealer over fastener heads per GenFlex specifications and details. This product is NOT intended to be used as a seam sealant.

Method of Application

1. Apply Termination Caulk only on clean, dry surfaces in accordance with GenFlex specifications and details. Surfaces onto which the sealant is used shall be free from loose concrete, stone, mortar, foreign materials, and other contaminants.
2. Use Termination Caulk to ensure watertight seal between the Termination Bar and parapet wall.
3. Apply sealant into the reservoir channel creating a 100% seal between the termination bar and the wall.
4. Termination Caulk can be applied directly from the cartridge using a standard handgun.
5. Apply Termination Caulk to substrates above 40 °F (4 °C).

Coverage Rate

300 ml (10 oz.) cartridge seals 24 linear feet in a ¼" x ¼" joint

Clean Up

- Use mineral spirits or GenFlex Cleaner while material is fresh.
- After Termination Caulk cures, it can be removed by abrasion or mechanical means.

Storage

- Store in original unopened container indoors at temperatures between 60 °F (16 °C) - 80 °F (27 °C).
- Do not store it on the roof in direct sunlight.
- When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

12 months; shelf life will be shortened if exposed to elevated temperatures.

Precautions

- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Store at temperature of 80 °F (27 °C) or below for maximum shelf life.
- Keep out of reach of children.
- Keep away from eyes.
- Do not thin.
- Review Safety Data Sheet prior to use.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

V.O.C. Content: 111 g/L

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Flashing Property	Typical Performance
Color	Grey
Base	Polyurethane
Solids	92.5% ± 2
Tooling Time	Less than 20 minutes
UV & Ozone Resistance	Excellent
Specific Gravity	1.186 ± 0.024
Cure Systems	Moisture Activated

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.