

Product Data Sheet



GenFlex EPDM Boot

Item Description	Item Number
Black	W590010100
*10 boots with 10 clamps per carton	

Description

GenFlex EPDM Boot is an injection-molded component that makes installations simple and easier than using field fabricated or field flashing procedures and details. The boot is specifically designed to be used in roofing applications for flashing of round penetrations. The pipe boot will fit various penetrations and shall be cut to the correct pipe diameter before installations. Please refer to the GenFlex EPDM specifications and details for specific information.

Method of Application

1. Membrane around penetration must be clean of prior flashing or foreign materials.
2. Measure the outside diameter of the penetration to be flashed and cut along the top edge of the ring corresponding to that size.
3. Clean the EPDM membrane with Cleaner and install the Pipe using G-400 Seam Adhesive per current GenFlex Specifications to attach the flange to the membrane.
4. Install Waterstop to the penetration making sure the sealant will coincide with the top inside edge of the boot.
5. Install the clamp ring and edge caulk to the top of the flashing.

Storage

- Store in original unopened container indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.
- Do not store in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

Precautions

- Take care when moving, transporting, and handling, etc., to avoid sources of punctures and physical damage.
- Contact GenFlex Systems Technical Department for specific recommendations.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Typical Value
Color	Black
Base	Modified EPDM
Thickness	.055" - .075" (1.4 mm – 1.9 mm)
Size	Universal – Fits 1" O.D. to 6.875" O.D. (25.4 mm to 174.6 mm)
Clamp	Stainless Steel – Worm Gear Type
Pipe Flange O.D.	13" (330 mm)

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.