

Product Data Sheet



SBS Glass Torch Base 1.5

| Item Description | Item Number |
|---------------------|-------------|
| 1 roll (1.5 square) | W81FSP0925 |

Description

GenFlex SBS Glass Torch Base 1.5 is a modified bitumen membrane featuring a blend of SBS (Styrene-Butadiene-Styrene) rubber polymer and high-quality asphalt reinforced with a 1.8 lb/100 ft² (90 g/m²) strong non-woven fiberglass mat intended to be installed with a roofing torch. The addition of SBS rubber polymer optimizes the asphalt blend to increase its natural waterproofing properties, adding elongation, elasticity, and flexibility to the sheet. The inorganic fiber glass reinforcement resists moisture absorption. It also provides strength and stability to the product, yielding a membrane that resists natural forces and other factors on the rooftop. SBS Glass Torch Base 1.5 membrane is designed specifically as a base layer for use with GenFlex SBS Modified Bitumen Systems.

GenFlex SBS systems that use SBS Glass Torch Base 1.5 are ideal for use on both new construction and reroofing projects. **NOTE:** Meets or exceeds performance requirements of ASTM D 6163, Type I, Grade S.

| Product Packaging | |
|-------------------|--|
| Property | Value |
| Roll width | 3 ft 3 in (1 m) |
| Roll length | 50 ft (15.24 m) |
| Net coverage | 150 ft ² (13.9 m ²) |
| Roll weight | 98 lb (44.45 kg) |
| Pallet size | 48 in x 39 in (1.2 m x 1 m) |
| Rolls per pallet | 25 |
| Weight per pallet | 2450 lb (111.3 kg) |

Method of Application

Refer to current GenFlex Technical Specifications for additional instructions.

1. SBS Glass Torch Base 1.5 must be installed by fully heat welding the membrane to an appropriate substrate.
2. Please see the SBS Application Guide at www.GenFlex.com for detailed information regarding the application for SBS Glass Torch Base 1.5.

Acceptable Immediate Substrates for Heat Welded Application

- Structural Concrete (must be clean, dry, properly cured, and primed with ASTM D-41 primer).
- Existing Smooth Surface BUR or SBS Modified Bitumen (must be clean, smooth, and primed with ASTM D-41 primer).
- DensDeck® Prime, SECUROCK® Gypsum Fiber.

NOTE: Please reference the Asphalt Roofing Systems Guide for Applicators and Designers available at www.genflex.com for detailed information regarding the type of deck and insulation in use.

Storage

- The material should be stored out of the weather in a clean, dry area in its original unopened packaging at a minimum of 50 °F (10 °C) and a maximum of 100 °F (38 °C) so that it will be 50 °F (10 °C) or above at the time of application. Do not stack GenFlex SBS Glass Torch Base 1.5 more than two (2) pallets high.
- If the material must be stored temporarily on the roof before application, it must be elevated from the roof surface on a pallet, stored on end, and covered from the weather with a light-colored opaque tarp in a neat, safe manner that does not exceed the allowable load limit of the storage area.

Precautions

- Take care when transporting and handling GenFlex Modified Bitumen rolls to avoid punctures and other types of physical damage.
- Isolate waste products, petroleum products, grease, oil (mineral and vegetable) and animal fats from all GenFlex Modified Bitumen membranes.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Beech Grove, IN



NOTE: LEED® is a registered trademark of the U.S. Green Building Council

| Typical Properties | | | |
|--|--------------|---|---|
| Property | Test Method | ASTM Standard Req'd Value | Typical Performance |
| Product Thickness | D5147 | 80 mil (3.3 mm) | 90 mil (3.9 mm) |
| Net mass | D146 | 45 lb/100 ft ² (2197 g/m ²) | 58 lb/100 ft ² (2832 g/m ²) |
| Bottom side coating | D5147 | 40 mil (1.02 mm) | 47 mil (1.19 mm) |
| Peak load at 0 °F (-18 °C) | D5147 | 70 lbf/in, MD (12.3 kN/m) 70 lbf/in, XMD (12.3 kN/m) | 75 lbf/in, MD (13.1 kN/m, MD) 75 lbf/in, XMD (13.1 kN/m, MD) |
| Elongation at Peak load at 0 °F (-18 °C) | D5147 | 1%, MD; 1%, XMD | 3%, MD; 3%, XMD |
| Peak load at 73 °F (23 °C) | D5147 | 30 lbf/in, MD (5.3 kN/m) 30 lbf/in, XMD (5.3 kN/m) | 40 lbf/in, MD (7 kN/m) 40 lbf/in, XMD (7 kN/m) |
| Elongation at Peak Load at 73 °F (23 °C) | D5147 | 2%, MD; 2%, XMD | 3%, MD; 3%, XMD |
| Ultimate Elongation at 5% of Peak Load 73 °F (23 °C) | D5147 | 3%, MD; 3%, XMD | 15%, MD; 15%, XMD |
| Tear Strength at 73 °F (23 °C) | D5147, D4073 | 35 lbf, MD (246 N) 35 lbf, XMD (246 N) | 40 lbf, MD (178 N, MD) 40 lbf, XMD (178 N, MD) |
| Heat Aged Peak Load at 0 °F (-18 °C) | D5147 | 70 lbf/in, MD (12.3 kN/m) 70 lbf/in, XMD (12.3 kN/m) | 75 lbf/in, MD (13.1 kN/m, MD) 75 lbf/in, XMD (13.1 kN/m, MD) |
| Heat Aged Elongation at Peak Load at 0 °F (18 °C) | D5147 | 1%, MD; 1%, CD | 3%, MD; 3%, CD |
| Heat Aged Peak Load at 73 °F (23 °C) | D5147 | 30 lbf/in, MD (5.3 kN/m) 30 lbf/in, XMD (5.3 kN/m) | 40 lbf/in, MD (7 kN/m) 40 lbf/in, XMD (7 kN/m) |
| Heat Aged Elongation at Peak Load at 73 °F (23 °C) | D5147 | 2%, MD; 2%, CD | 3%, MD; 3%, CD |
| Heat Aged Ultimate Elongation at 5% of Peak Load 73 °F (23 °C) | D5147 | 3%, MD; 3%, CD | 15%, MD; 15%, CD |
| Low Temperature Flexibility | D5147 | 0 °F (-18 °C) | -15 °F (-26 °C) |
| Dimensional Stability | D5147, D1204 | 0.5%, MD; 0.5%, XMD | 0.2%, MD; 0.2%, XMD |
| Compound Stability @ 215 °F (102 °C) | D5147 | No failures | 270 °F (132 °C) |

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.