

Product Data Sheet



All Purpose LVOC Cleaner

Item Description	Item Number
3-gallon (11.4 liter) pail *Approximately 20 lb (9 kg)	W590030121

Description

GenFlex All Purpose LVOC Cleaner is designed to clean and prepare GenFlex single-ply membranes to be welded, or to receive GenFlex Primers, Adhesives or Sealants, as noted in GenFlex specifications and details

Method of Application

1. Surfaces to be welded, or to receive primer, adhesive or sealant shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminates using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with GenFlex All Purpose LVOC Cleaner, moving in circular motions with heavy pressure over affected areas. Membrane with caked dirt, including in-service thermoplastic membranes, should be scrubbed using a GenFlex Scrub Pad and Handle wetted with All Purpose LVOC Cleaner, followed by wiping with clean rags to remove contaminates. On thermoplastic surfaces, the wipe with All Purpose LVOC Cleaner should be in one direction, flipping the rag often to avoid transferring contaminates.
3. Allow surfaces cleaned with GenFlex All Purpose LVOC Cleaner to dry completely (usually within 10 to 30 minutes) before welding or applying primer, adhesive or sealant per current GenFlex specifications and details.

Storage

- Store in original unopened container, at temperatures between 60 °F (16 °C) and 80 °F (27 °C), away from all sources of direct heat and ignition, until ready for use. This is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.
- Shelf life of 24 months can be expected when stored in original unopened container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).

Coverage Rate

200-250 ft²/gallon (4.9 - 6.1 m²/L) on one side.

Precautions

- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not permitted.
- Use of solvent-resistant neoprene gloves is required.
- Avoid contact with eyes and skin.
- Avoid breathing vapors.
- Do not take internally.
- Cover container tightly when not in use.
- Use only in well-ventilated areas.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: South Bend, IN

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Test Method
Solvents	Solvent Blend of Acetone and Mineral Spirits
Viscosity	Very thin, free flowing
Weight / Gallon	6.593 ± 0.329 lb/gal (790 ± 39.42 g/L)
V.O.C. Content	Less than 250 g/L

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.