


Product Data Sheet



GenFast Lite Deck Bar

Item Description	Item Number
18 ga. (13 mm) Steel Batten Bar	W590055007

Description

The Lite Deck Bar is made of 18-gauge (1.33 mm) steel. The Lite Deck Bar is designed to be used with GenFast Lite Deck Fasteners for membrane attachment into lightweight concrete, cementitious wood fiber and gypsum roof decks for detailing purposes.

Method of Application

Attach batten strips to the roof substrate or penetration using the Lite Deck Fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners. Round edges if bar is cut.

Storage

- Bars should be protected from moisture and kept dry at all times.
- If stored outdoors, place on skids in dry area and cover with a breathable tarp.
- Store in original containers only.

Precautions

- Do not over/under drive fasteners.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Total Recycled Content: 51% (Formula for total % is Post-Consumer + ½ Pre-Consumer)
 Post-Consumer Recycled Content: 41%
 Pre-Consumer Recycled Content: 19%

Manufacturing Location: Cleveland, Ohio

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

PDS 1209
 April 7, 2026
 Sales: (800) 428-4442
 Technical: (800) 443-4272
 Page 1

Product Packaging	
Per Piece	10' (3.048 m)
Per Tube	50 Pieces
Weight Per Tube	80 lb (36.32 kg)

Typical Properties	
Property	Test Method
Material	18 Gauge (1.3 mm) Steel
Length	10' (3.048 m)
Hole Spacing	6" (152.4 mm)

Please contact Amrize Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published GenFlex product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.