



- NOTE:
1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
  2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
  3. REFER TO EZT-BT-16 & EZT-BT-17 FOR MEMBRANE SECUREMENT AT CORNERS.
  4. APPROPRIATE GENFLEX MEMBRANE ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR ADHERED SYSTEMS.
  5. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.
  6. FOR SINGLE LIP TERMINATION BARS, ENSURE THAT THE TOP LINE FACES UPWARD

**WARRANTY MEMBRANE REQUIREMENTS:**  
**15-YEAR**  
 TPO - 45 MIL  
**20-YEAR**  
 TPO - 60 MIL

	<b>BASE TIE-IN WITH TERMINATION BAR FASTENED TO WALL OR CURB</b>		MAXIMUM WARRANTY: 20 Years	
	MATERIAL: EZ TPO	ACCEPTABLE SYSTEMS: ALL	ISSUE / REVISION DATE: 04/14/2026	DETAIL NO. <b>EZT-BT-02A</b>
GENFLEX: (800) 443-4272 www.genflex.com			NOT TO SCALE	