



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. INSTALL METAL WORK TO SMACNA RECOMMENDATIONS
4. WOOD NAILER BY OTHERS MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.
5. FLANGE OF METAL MUST BE FULLY SUPPORTED BY WOOD AND TERMINATED AT LEAST ½" (13 mm) FROM EDGE OF WOOD.
6. INSTALL TPO COATED METAL WITH 1/8" (3.175 mm) MIN. TO 1/4" (6.35 mm) MAX BETWEEN ADJOINING SECTIONS.
7. SEE EZT-BT-09A & EZT-BT-09B FOR DETAILED INSTALLATION INSTRUCTIONS.
8. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR
 TPO - 45 MIL
20-YEAR
 TPO - 60 MIL



BASE TIE-IN WITH TPO COATED METAL (WITH BRAKE) SPLICE

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/14/2026

DETAIL NO.

EZT-BT-09

GENFLEX: (800) 443-4272 www.genflex.com

NOT TO SCALE