



NOTE:

1. REFER TO THE GENFLEX™ WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO DETAIL EZT-LS-01 OR EZT-LS-02 FOR WELD WIDTH.
3. INSTALL METAL WORK TO SMACNA RECOMMENDATIONS
4. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES.
5. FLANGE OF METAL MUST BE FULLY SUPPORTED BY WOOD AND TERMINATED AT LEAST 1/2" (12.7 mm) FROM EDGE OF WOOD.
6. INSTALL TPO COATED METAL WITH 1/8" (3.175 mm) MIN. TO 1/4" (6.35 mm) MAX BETWEEN ADJOINING SECTIONS.
7. SEE EZT-BT-11A & EZT-BT-11B FOR DETAILED INSTALLATION INSTRUCTIONS.
8. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO EZT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

WARRANTY MEMBRANE REQUIREMENTS:
15-YEAR TPO - 45 MIL
20-YEAR TPO - 60 MIL



TPO COATED METAL SPLICE

MATERIAL: EZ TPO

ACCEPTABLE SYSTEMS: ALL

GENFLEX: (800) 443-4272 www.genflex.com

MAXIMUM WARRANTY: 20 Years

ISSUE / REVISION DATE:

04/14/2026

NOT TO SCALE

DETAIL NO.

EZT-BT-11